

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME I LIGHT LIST, 2000

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
9006	- NORTH JETTY LIGHT 4	42 49 06 N 70 48 12 W	Q R	15	4	TR on skeleton tower.	
					*		36/00
14756	Cotuit Harbor Junction Buoy CS	41 36 42 N 70 25 48 W				Red and green bands; nun.	Maintained from Jun. 1 to Dec. 1. Private aid.
	*						36/00
<p>*Change Heading to Read: *Cotuit Entrance Channel</p> <p><i>Aids maintained from Jun. 1 to Nov. 1 unless otherwise noted.</i></p>							
14760.1	- Buoy 1	41 35 48 N 70 25 48 W				Green can.	Private aid.
							36/00
<p>*Add Heading: *Cotuit Harbor</p> <p><i>Aids maintained from Jun. 1 to Nov. 1 unless otherwise noted.</i></p>							
14760.36	- Buoy 1					Green can.	Private aid.
							36/00

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2000

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
2735	- REAR LIGHT 800 yards, 334° from front light.		F G	110		White skeleton tower, small white house.	Visible on rangeline only. Lighted throughout 24 hours.
						*	* 36/00
2760	- LIGHT 3	39 33 06 N 75 37 18 W	FI G 2.5s	20	3	SG on pile.	Higher intensity towards center span of bridge.
						*	36/00
2810	DELAWARE CITY LIGHT 1	39 34 42 N 75 35 06 W	FI G 4s	14	4	SG on pile.	Light equipment removed when endangered by ice.
						*	36/00
Delaware River (Main Channel)							
2830	FORT DELAWARE LIGHT 5N	39 35 24 N 75 33 54 W	FI G 6s	17	5	SG on pile.	
						*	36/00
3005	- RANGE FRONT LIGHT	39 43 24 N 75 32 00 W	Q G	20		KRW on skeleton tower.	Higher intensity on rangeline. Lighted throughout 24 hours.
							* 36/00
3010	- RANGE REAR LIGHT 285 yards, 293° from front light.		Iso G 6s	38		KRW on skeleton tower.	Higher intensity on rangeline. Lighted throughout 24 hours.
							* 36/00

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceeding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2000

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
3125	GRUBBS LANDING LIGHT	39 47 06 N 75 27 48 W	FI W 4s (R sector)	16	W 7 R 5	NG on skeleton tower.	Red from 205° to 290°. * 36/00
3230	- FRONT LIGHT	39 51 12 N 75 19 54 W	Iso G 6s	62		On square skeleton tower.	Visible on range line only. Lighted throughout 24 hours. * 36/00
3235	- REAR LIGHT 548 yards, 050.8° from front light.		F G	95		On square skeleton tower.	Visible on range line only. Lighted throughout 24 hours. * 36/00
3415	- RANGE FRONT LIGHT	39 53 18 N 75 11 36 W	Q G	33		On skeleton tower.	 * 36/00
3420	- RANGE REAR LIGHT 229 yards, 021.5° from front light.		Oc G 4s	64		On skeleton tower.	 * 36/00
*3507	CEPOC Buoy A					Yellow.	Private aid. 36/00
*3512	CEPOC Buoy B					Yellow.	Private aid. 36/00
*3527.1	CEPOC Buoy C					Yellow.	Private aid. 36/00
*3527.2	CEPOC Buoy D					Yellow.	Private aid. 36/00
*3527.3	CEPOC Buoy E					Yellow.	Private aid. 36/00
*3527.4	CEPOC Buoy F					Yellow.	Private aid. 36/00

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME III LIGHT LIST, 2000

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
830	<i>NOAA Data Lighted Buoy 41002</i>	32 17 06 N 75 13 00 W	FI (4) Y 20s			Yellow boat-shaped with mast.	 * 33/00
1660 30455	STEINHATCHEE RIVER LIGHT 1	29 39 24 N 83 27 24 W	FI G 4s	30	5	SG on pile.	 * 32/00

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME III LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
1985	Jones Creek South Net Obstruction Daybeacon	33 16 48 N 79 11 30 W				NW on dolphin worded DANGER PILINGS.	Private aid.
	*						36/00
2445	- South Jetty Buoy 1	32 43 54 N 79 51 06 W				Green can.	
	*	*				*	36/00
2450	- South Jetty Buoy 2	32 43 54 N 79 51 06 W				Red nun.	
	*					*	36/00
2800	- UPPER RANGE REAR LIGHT 103 yards, 113° from front light.		Iso W 6s	43		KRW on skeleton tower on piles.	Visible 2° each side of rangeline.
	*						30/00
2970	- RANGE B REAR LIGHT 39 yards, 216° from front light.		Iso G 6s	21		KRW on dolphin.	Visible 2° each side of rangeline.
	*					*	* 32/00
3385	- Daybeacon 22					TR on pile.	
	*					*	36/00
3390	- Daybeacon 23					SG on pile.	
	*					*	36/00
3490	- Daybeacon 36					TR on pile.	
	*					*	36/00
3495	- Daybeacon 37					SG on pile.	
	*					*	36/00
Ashley River							
3570 34590	- APPROACH RANGE FRONT LIGHT	32 46 24 N 79 57 06 W	Q R FI R 4s	20 21	3	KRW-I on dolphin.	Visible 2° each side of rangeline. Higher intensity on rangeline. Passing light visible all around.
							* 36/00
5380	- Daybeacon 56					TR on pile.	
	*					*	36/00
5385	- Daybeacon 57					SG on pile.	
	*					*	36/00
5390	- Daybeacon 57A					SG on pile.	
	*					*	36/00

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME III LIGHT LIST, 2000

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
5395	- Daybeacon 58					SG on pile.	
	*						36/00
6026	CLOISTER HOTEL NORTH OBSTRUCTION LIGHT	31 10 48 N 81 20 48 W	FI W 2.5s	15	5	NB on pile worded DANGER OBSTRUCTION.	Private aid.
	*						36/00
6027	CLOISTER HOTEL SOUTH OBSTRUCTION LIGHT	31 10 48 N 81 20 48 W	FI W 2.5s	15	5	NB on pile worded DANGER OBSTRUCTION.	Private aid.
	*						36/00
St. Marys Entrance							
6525	- RANGE FRONT LIGHT	30 42 30 N 81 27 54 W	F W Q W	26 30		KRW on tower. On same structure as Cumberland Sound Obstruction Light.	Day range visible 0.5° each side of rangeline. Night range visible 2° each side of rangeline.
						*	* 36/00
6555	- Lighted Buoy 14A		FI R 6s		4	Red.	
	*		*			*	36/00
6560	- Lighted Buoy 15		FI G 4s		4	Green.	
	*		*			*	36/00
6575	- Lighted Buoy 16A		FI R 4s		3	Red.	
	*		*			*	36/00
6580	- Lighted Buoy 17		FI G 2.5s		3	Green.	
	*		*			*	36/00
6880 37785	- LOWER RANGE C FRONT LIGHT	30 43 18 N 81 29 12 W	Q R FI G 4s	15	5	KRW-I on dolphin.	Visible 2° each side of rangeline. Passing light visible from 212° to 159°.
						*	36/00
7000	- LIGHT 54		FI R 4s	16	4	TR on pile.	
				*			36/00
7005	- LIGHT 56		FI R 6s	16	4	TR on pile.	
				*			36/00
7010	- LIGHT 58		FI R 4s	16	3	TR on pile.	
				*			36/00
7015	- LIGHT 59		FI G 4s	16	4	SG on pile.	
				*			36/00
7020	- LIGHT 60		FI R 6s	16	4	TR on pile.	
				*			36/00

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME III LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
7025	- LIGHT 62		FI R 4s	16	3	TR on pile.	
				*			36/00
7030	- LIGHT 64		FI R 6s	16	4	TR on pile.	
				*			36/00
7035	- LIGHT 66		FI R 2.5s	16	3	TR on pile.	
				*			36/00
7040	- LIGHT 68		FI R 4s	16	3	TR on pile.	
				*			36/00
Lake Monroe							
9240	- Bar Daybeacon 1	28 50 04 N 81 18 58 W				SG on pile.	
		*					36/00
*9511 38911	St. Augustine Shoal Daybeacon	29 54 30 N 81 17 48 W				NW on pile worded DANGER SHOAL.	
							32/00
*Delete Heading: *Canaveral Harbor West Turning Basin							
9720	- LIGHT C						<i>Remove from list.</i>
							* 36/00
9725	- LIGHT D						<i>Remove from list.</i>
							* 36/00
9820	- ENTRANCE RANGE FRONT LIGHT	27 28 06 N 80 18 12 W	Q W	15		KRW on skeleton tower on piles.	Visible 2° each side of rangeline.
			*				33/00
9825	- ENTRANCE RANGE REAR LIGHT 1,296 yards, 259.6° from front light.		Iso W 6s	50		KRW on skeleton tower on piles.	Visible 2° each side of rangeline.
			*				33/00
Fort Pierce Inlet							
9940	- INNER HARBOR RANGE FRONT LIGHT	27 28 18 N 80 17 48 W	Q G	20		KRW on skeleton tower on piles.	Obscured from 129° to 355°. Higher intensity on rangeline.
	*		*				33/00
9945	- INNER HARBOR RANGE REAR LIGHT 265 yards, 061.7° from front light.		Iso G 6s	32		KRW on skeleton tower on piles.	Visible all around; higher intensity on rangeline.
	*		*				33/00

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME III LIGHT LIST, 2000

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*Delete Heading: *Fort Pierce Inlet							
9965	- Lighted Buoy 15	27 27 48 N 80 18 46 W	FI G 6s		4	Green.	36/00
9975 45125	- LIGHT 17	27 27 36 N 80 19 06 W	Q G	16	3	SG on pile.	
*							36/00
10330	- LIGHT 4	26 05 42 N 80 06 06 W	FI R 4s	16	5	TR on pile.	
						*	33/00
10335	- LIGHT 5		FI G 4s	16	5	SG on pile.	
				*		*	33/00
10380 47500	COAST GUARD STATION BREAKWATER LIGHT	26 05 24 N 80 06 48 W	F R	9	3	On breakwater.	
			*				27/00
12315	- LIGHT 87		FI G 4s	16	4	SG on pile.	
						*	36/00
Whitewater Bay							
15760	- Daybeacon 10	25 10 45 N 80 55 52 W				TR on pile.	
		*					36/00
Cormorant Pass							
15850	- Daybeacon 42	25 19 22 N 81 02 13 W				TR on pile.	
		*					36/00
16675	- South Approach Daybeacon 2	25 53 06 N 81 38 36 W				TR on pile.	
		*					36/00
*16925.5	- Daybeacon 5					SG on pile.	Private aid. 28/00
Gasparilla Sound							
21420	- Daybeacon 1	26 48 46 N 82 15 53 W				SG on pile.	
		*					36/00
*21456.4	Dona Bay East Obstruction Daybeacon	27 06 48 N 82 27 30 W				NW on pile worded DANGER SHOAL.	Private aid. 29/00

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME III LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*21456.6	Dona Bay West Obstruction Daybeacon	27 06 42 N 82 27 30 W				NW on pile worded DANGER SHOAL.	Private aid. 29/00
*21510.5	- Daybeacon 11A					SG on pile.	32/00
	*Change Heading to Read: *Lido Key Channel						
21550	- Daybeacon 6					TR on pile.	Private aid. 34/00
22550	- LIGHT 7		Q G	16	3	SG on pile.	 * 33/00
	Cut D Channel						
22700	- UPPER RANGE FRONT LIGHT	27 44 30 N 82 31 24 W	Q W FI W 6s	30 30	5	KRW on piles. On same structure as Cut F South Range Front Light.	Visible 2° each side of rangeline. Passing light visible all around. * * 36/00
22810	- NORTH RANGE FRONT LIGHT	27 47 42 N 82 31 24 W	FI G 2.5s	17		KRW on piles.	Visible 1° each side of rangeline. Lighted throughout 24 hours. Obstruction Light Q W visible all around on same structure. * * 28/00
*22810.5	- OBSTRUCTION LIGHT	27 47 42 N 82 31 24 W	Q W	12	5	KRW on piles.	Visible all around on same structure as North Range Front Light. 28/00
22815	- NORTH RANGE REAR LIGHT 1,551 yards, 359.6° from front light.		Iso G 6s	51		KRW on skeleton tower on piles.	Visible 1° each side of rangeline. Lighted throughout 24 hours. Obstruction Light FI W 4s visible all around on same structure. * * 28/00
*22815.2	- OBSTRUCTION LIGHT	27 47 42 N 82 31 24 W	FI W 4s	40	5	KRW on skeleton tower on piles.	Visible all around on same structure as North Range Rear Light. 28/00
23940	- LOWER RANGE FRONT LIGHT	27 48 30 N 82 34 42 W	FI W 2.5s	17		KRW on skeleton tower on piles.	Visible 1.5° each side of rangeline. Lighted throughout 24 hours. * * 28/00

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME III LIGHT LIST, 2000

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*Delete Headings: *TAMPA BAY (Chart 11417)							
*Tampa Bay *Cut K Channel							
23945	- LOWER RANGE REAR LIGHT 1,799 yards, 201.7° from front light.		Iso W 6s	51		KRW on skeleton tower on piles.	Visible 1.5° each side of rangeline. Lighted throughout 24 hours
				*			* 30/00
*Delete Headings: *TAMPA BAY (Chart 11417)							
*Tampa Bay *Little Manatee River							
24485	- Shoal Daybeacon	27 43 42 N 82 29 54 W				NW on pile worded DANGER SHOAL.	36/00
*Delete Headings: *TAMPA BAY (Chart 11417)							
*Tampa Bay *Point Pinellas Channel							
24725	- LIGHT 6		FI R 4s	12	3	TR on pile.	36/00
24735	- LIGHT 7	27 43 06 N 82 36 36 W	FI G 6s	16	3	SG on pile.	
*	*	*	*	*	*	*	* 28/00
*25470.5	- Channel Daybeacon 5A					SG on pile.	28/00
25500	- CHANNEL LIGHT 9	27 40 48 N 82 44 18 W	FI G 4s	15	4	SG on pile.	
	*						26/00
29555	-ENTRANCE LIGHT 32		Q R	18	3	TR on pile.	
	*						36/00
Steinhatchee River							
30455 1660	- LIGHT 1	29 39 24 N 83 27 24 W	FI G 4s	30	5	SG on pile.	
				*	*		32/00
30465	- LIGHT 5		FI G 6s	16	4	SG on pile.	
			*	*	*		26/00
30505	- LIGHT 17		FI G 4s	16	4	SG on pile.	
	*						36/00

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME III LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
Puerto Arecibo							
30725	- Buoy 1	18 28 48 N 66 42 17 W				Green can.	
		*					36/00
Army Terminal Channel							
30845	- Lighted Buoy A	18 26 55 N 66 06 26 W	FI (2+1) G 6s		3	Green and red bands.	
		*					36/00
Puerto Nuevo Channel							
30895	- Lighted Buoy 1	18 25 56 N 66 06 09 W	FI G 4s		4	Green.	
		*					36/00
31080	- Lighted Buoy 3		FI G 2.5s		4	Green.	
			*				36/00
31400	NAVY PIER LIGHTS (2)						<i>Remove from list.</i>
							* 30/00
32680	Johnson Reef Buoy JC	18 21 30 N 64 46 24 W				Yellow can.	Private aid.
	*					*	* 27/00
Watergate Channel							
33565	- Lighted Buoy 1	19 56 24 N 75 08 54 W	Q G		3	Green.	
		*					26/00
37430	Umbrella Cut Daybeacon A6					TR-TY on pile.	
	*						26/00
*38905.5	- Lighted Buoy 59	29 54 36 N 81 17 42 W	FI G 2.5s			Green.	
							32/00
*38911 9511	St Augustine Shoal Daybeacon	29 54 30 N 81 17 48 W				NW on pile worded DANGER SHOAL.	
							32/00
*Change Heading to Read: *Florida Dept of Transportation Bridge of Lions							
39052	- NORTH BREASTING LIGHT	29 54 06 N 81 18 18 W	FI W 4s	13		On dolphin.	Private aid.
							34/00

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME III LIGHT LIST, 2000

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*Delete Heading:							
*Florida Department of Transportation State Road							
39092	- NORTH BREASTING LIGHT						<i>Remove from list.</i>
							* 33/00
39093	- CENTER BREASTING LIGHT						<i>Remove from list.</i>
							* 33/00
39094	- SOUTH BREASTING LIGHT						<i>Remove from list.</i>
							* 33/00
Halifax River							
39835	- LIGHT 2	29 21 35 N 81 04 46 W	F I R 4s	16	3	TR-TY on dolphin.	
		*					36/00
Banana River (North) Channel A							
41835	- Daybeacon 1	28 24 27 N 80 37 15 W				SG on pile.	
		*					36/00
Banana River (North) Channel B							
42045	- Daybeacon 1	28 35 30 N 80 36 32 W				SG on pile.	
		*					36/00
*42491	- RANGE FRONT LIGHT	28 12 48 N 80 36 54 W	F W	40		KRW on piles.	Private aid.
							33/00
*42492	- RANGE REAR LIGHT 287 yards, 084° from front light.		F W	45		KRW on piles.	Private aid.
							28/00
47500 10380	COAST GUARD STATION BREAKWATER LIGHT	26 05 24 N 80 06 48 W	F R	9	3	On breakwater.	
			*				27/00
49680	Featherbed Bank East Daybeacon 1	25 32 22 N 80 12 30 W				SG on pile.	
		*					36/00
St. Lucie River (North Fork)							
50840	- Daybeacon 1	27 12 03 N 80 16 01 W				SG on pile.	
		*					36/00
54750	- LIGHT 93	26 31 42 N 81 59 42 W	F I G 2.5s	16	5	SG-SY on pile.	
	*	*	*	*	*		32/00

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

SUMMARY OF CORRECTIONS TO C. G. LIGHT LIST, VOLUME III LIGHT LIST, 2000

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
55425	- LIGHT 20	26 28 42 N 82 06 36 W	F I R 4s	16	3	TR-TY on pile.	
		*					26/00
*55775.5	- Daybeacon 41					SG on pile.	32/00
Useppa Island							
56150	- Daybeacon 2	26 40 20 N 82 13 09 W				TR on pile.	
		*					36/00
57275.5	- Daybeacon 16					TR-TY on pile.	
						*	27/00
Ozona Channel							
62050	- LIGHT 2	28 04 12 N 82 48 09 W	F I R 4s	16	3	TR on pile.	
		*					36/00

CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV LIGHT LIST, 2000

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
9560	- LIGHT 6	30 06 03 N 89 48 54 W	F I R 4s	17	4	TR on dolphin.	
		*					36/00
9715	IRISH BAYOU LIGHT 1	30 08 30 N 89 51 32 W	F I G 6s	17	4	SG on dolphin.	
		*					36/00
9745	- LIGHT 2	30 13 06 N 89 51 58 W	F I R 4s	17	5	TR on dolphin.	
		*					36/00
9785	- Daybeacon 10	30 14 55 N 89 51 56 W				TR on pile.	
		*					36/00
Bayou Castine							
10005	- Entrance Daybeacon 1	30 20 48 N 90 03 50 W				SG on pile.	
		*					36/00
10015	- LIGHT 3	30 20 50 N 90 03 48 W	F I G 4s	26	4	SG on concrete structure.	
		*					36/00

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV LIGHT LIST, 2000

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
33330	- JUNCTION LIGHT	29 49 18 N 90 04 04 W	FI (2+1) R 6s		4	JR-TY on skeleton tower on piles.	Higher intensity beam up Algiers Alternate Route and down Bayou Barataria. * 36/00
35005	Lake Como Entrance Daybeacon 1						Remove from list. * 36/00
35010	Lake Como Entrance Daybeacon 2						Remove from list. * 36/00

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI LIGHT LIST, 2000

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
1858.7	- Coronado Bridge Lighted Mooring Buoy C	32 41 23 N 117 09 23 W	FI W 4s			White can buoy with blue band.	Private aid. * 36/00
2848	- Lighted Mooring buoy A	33 43 42 N 118 08 06 W	FI W 4s			White spherical buoy with blue band.	Private aid. * 36/00
3018	- Lighted Mooring Buoy D	33 43 30 N 118 12 00 W	FI W 4s			White spherical buoy with blue band.	Private aid. * 36/00
3023.1	- Lighted Mooring Buoy C	33 44 24 N 118 11 06 W	FI W 4s			White spherical buoy with blue band.	Private aid. * 36/00
3296	- Lighted Mooring Buoy B	33 42 36 N 118 16 39 W	FI W 4s			White spherical buoy with blue band.	Private aid. * 36/00
*9818	- Entrance Junction Gong Buoy S	45 34 02 N 123 58 17 W				Red and green bands.	36/00

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII LIGHT LIST, 2000

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*11976	- Daybeacon 39A					SG on pile.	36/00
*12704	Bow Island Buoy 4	46 02 01 N 83 49 30 W				Red nun.	36/00

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII LIGHT LIST, 2000

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*12746	Quarry Island Buoy 8A	46 02 00 N 83 44 01 W				Red nun.	Maintained from May 14 to Oct. 28.

36/00

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.