

**SECTION II**

CORRECTIONS TO C. G. LIGHT LIST, VOLUME I LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
4130	- Breakwater Light	44 06 15 N 69 04 39 W	FI W 5s	39	17	White square tower on corner of fog-signal house, on granite pier.	HORN: 1 blast ev 15s (2s bl).
		*					* 20/01
*37261	- Channel Lighted Buoy 1		FI G 4s		4	Green.	
							20/01
37265	- Channel Junction Lighted Whistle Buoy KV	40 38 57 N 74 03 52 W	FI (2+1) R 6s		4	Red and green bands.	RACON: K (-•-)
		*					20/01

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2001							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
<b>Chesapeake and Delaware Canal</b>							
<i>The north and south banks of the Chesapeake and Delaware Canal between Sandy Point, Maryland, and Reedy Point, Delaware are lighted by mercury vapor luminaries, spaced 500 feet apart and are supported on poles at a height of 25 feet mean high water. They are designed to illuminate the bank at the waters edge to assist ships navigating the canal at night. (Maintained by U.S. Army Corps of Engineers).</i>							
2745	- Junction Lighted Bell Buoy CD	39 33 52 N 75 33 18 W	FI (2+1) R 6s		4	Red with green band.	Replaced by LIB of lower intensity from Dec. 1 to Mar. 15.
		*					20/01
3320	BILLINGSPOINT RANGE FRONT LIGHT	39 50 30 N 75 17 15 W	Iso R 2s	21		On tower.	Visible on range line only. Lighted throughout 24 hours.
		*	*			*	* 20/01
3325	BILLINGSPOINT RANGE REAR LIGHT 479 yards, 250° from front light.		Oc R 4s	43		On tower.	Visible on range line only. Lighted throughout 24 hours.
						*	* 20/01
7585	USN Aerial Gunnery Area Lighted Bell Buoy D	38 13 05 N 76 19 15 W	FI Y 2.5s		4	Yellow.	Replaced by nun when endangered by ice.
		*					20/01
7682	- Lighted Buoy 78A		FI R 2.5s		5	Red.	Replaced by LIB of lower intensity when endangered by ice.
							* 20/01
8100	- Lighted Buoy 18		Q R		4	Red.	Replaced by LIB of lower intensity from Dec. 1 to Mar. 15.
							* 20/01

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

## SECTION II

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2001

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
8105	- Lighted Buoy 19		FI G 4s		4	Green.	Replaced by LIB of lower intensity from Dec. 1 to Mar. 15.  * 20/01
8360	- Lighted Buoy 4	39 05 39 N 76 17 54 W	Q R		4	Red.	Replaced by LIB of lower intensity from Dec. 1 to Mar. 15.  * 20/01
8435	- Lighted Buoy 9	39 10 14 N 76 24 47 W	FI G 2.5s		4	Green.	Replaced by LIB of lower intensity from Dec. 1 to Mar. 15.  20/01
8440	- Lighted Buoy 10	39 10 21 N 76 24 43 W	FI R 2.5s		4	Red.	Replaced by LIB of lower intensity from Dec. 1 to Mar. 15.  * 20/01
8520	- Lighted Buoy 28	39 12 32 N 76 15 00 W	FI R 4s		4	Red.	Replaced by LIB of lower intensity from Dec. 1 to Mar. 15.  20/01
9223	LA-17 Lighted Mooring Buoy						Remove from list.  * 20/01
12130	SWANN POINT SHOAL CHANNEL RANGE FRONT LIGHT	37 13 19 N 76 47 42 W	FI W 2.5s	16		On multi-pile structure.	Lighted throughout 24 hours. Visible all around; higher intensity on range line.  * 20/01
12135	SWANN POINT SHOAL CHANNEL RANGE REAR LIGHT 1,030 yards, 083° from front light.		ISO R 6s	62		On white tower.	Visible all around. Lighted throughout 24 hours.  * 20/01
18620	- Lighted Buoy 6	38 48 45 N 77 02 01 W	FI R 2.5s		4	Red.	Replaced by LIB of lower intensity when endangered by ice.  * 20/01
<b>Alexandria Channel</b>							
18660	- Lighted Buoy 7A	38 49 50 N 77 01 46 W	FI G 4s		4	Green.	Replaced by LIB of lower intensity when endangered by ice.  * 20/01
18705	Hains Point Junction Lighted Buoy HP	38 51 06 N 77 01 20 W	FI (2+1) G 6s		4	Green and red bands.	Replaced by LIB of lower intensity when endangered by ice.  * 20/01

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

## SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2001							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
18735	- Lighted Buoy 3		FI G 4s		4	Green.	Replaced by LIB of lower intensity when endangered by ice.  * 20/01
*19680	- LIGHT 5		FI G 4s	15	3	SG on pile.	20/01
21245	- Buoy 2	39 15 25 N 76 35 44 W				Red nun.	
		*					20/01
	<b>*Delete Heading: *Wicomico Creek</b>						
23855	- RANGE FRONT LIGHT						Remove from list.  * 20/01
23860	- RANGE REAR LIGHT 120 yards, 102° from front light.						Remove from list.  * 20/01
	<b>*Add Heading: *Wicomico Creek</b>						
23865	- Daybeacon 2					TR on pile.	20/01
24785	- Entrance Buoy 4	38 34 28 N 76 22 25 W				Red nun.	
		*					20/01
28964	- LIGHT 27	35 04 47 N 76 00 18 W	Q G	15	3	SG on pile.	
				*			20/01
28965	- LIGHT 29		FI G 4s	15	3	SG on pile.	
				*			20/01

CORRECTIONS TO C. G. LIGHT LIST, VOLUME III LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
	<b>*Delete Heading: *Key Biscayne FAD</b>						
900	Key Biscayne Northwest FAD Buoy	25 42 50 N 80 05 28 W				Yellow can.	Private aid.  * 20/01
	*	*					
905	Key Biscayne Northeast FAD Buoy					Yellow can.	Private aid.  * 20/01
	*						

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

## SECTION II

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME III LIGHT LIST, 2000

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
910	Key Biscayne Southwest FAD Buoy					Yellow can.	Private aid.  * 20/01
915	Key Biscayne Southeast FAD Buoy					Yellow can.	Private aid.  * 20/01
920	<b>Fowey Rocks Light</b> On outer line of reefs.	25 35 24 N 80 05 48 W	<b>Fl W 10s</b> <b>(2R sectors)</b>	110	W 15 R 10	Brown octagonal, pyramidal skeleton tower, enclosing white stair cylinder and octagonal dwelling; pile foundation.	White from 188° to 359° and from 022° to 180°, red in intervening sectors. RACON: O (---).  20/01
	<b>*Delete Heading: *Big Bend</b>						
1635	- LIGHT 12						<i>Remove from list.</i>  * 20/01
1640	- LIGHT 14						<i>Remove from list.</i>  * 20/01
	<b>*Delete Heading: *Big Bend</b>						
1650	- LIGHT 16						<i>Remove from list.</i>  * 20/01
1655	- LIGHT 18						<i>Remove from list.</i>  * 20/01
1670	- LIGHT 20						<i>Remove from list.</i>  * 20/01
1675	- LIGHT 22						<i>Remove from list.</i>  * 20/01
14965	- Range Rear Daybeacon 45 yards, 076° from front daybeacon.					KRW on dolphin.	Maintained by U.S. Navy.  * 20/01
16790.02	- Daybeacon 2					TR on pile.	Private aid.  * 20/01
16790.04	- Daybeacon 4					TR on pile.	Private aid.  * 20/01
16790.06	- Daybeacon 8					TR on pile.	Private aid.  * 20/01

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

**SECTION II**

CORRECTIONS TO C. G. LIGHT LIST, VOLUME III LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
<b>Matanzas Pass Channel</b>							
18085	- LIGHT 1	26 27 39 N 81 58 29 W	<b>FI G</b> 2.5s	16	4	SG on pile.	
		*					20/01
59560	- LIGHT 47		<b>FI G</b> 2.5s	16	3	SG-SY on pile.	
	*		*	*	*		20/01
CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
973	<i>Murphy-111-7 Lighted Buoy</i> Marks subsea installation.						<i>Remove from list.</i>
							* 20/01
3005	- Range C Front Daybeacon	29 52 54 N 85 22 30 W				KRW on skeleton tower on piles.	
			*	*	*		* 20/01
*3007	- RANGE C FRONT PASSING LIGHT		<b>Q W</b>	28	5	On same structure as St. Joseph Bay Entrance Range C Front Daybeacon.	
							20/01
3010	- Range C Rear Daybeacon 1,525 yards, 119.5° from front daybeacon.					KRW on skeleton tower on piles.	
			*	*	*		* 20/01
*3013	- RANGE C REAR PASSING LIGHT		<b>FI W</b> 2.5s	22	5	On same structure as St. Joseph Bay Entrance Range C Rear Daybeacon.	
							20/01
3175	- RANGE A FRONT LIGHT	30 08 48 N 85 41 36 W	<b>FI W</b> 2.5s	20		KRW on skeleton tower on piles.	Lighted throughout 24 hours. Visible all around, higher intensity on range line.
			*	*	*		* 20/01
3930	CAUCUS CHANNEL RANGE FRONT LIGHT	30 19 54 N 87 18 54 W	<b>Q G</b>	34		KRW on skeleton tower on piles.	Visible all around, higher intensity on range line.
			*	*	*		20/01
4075 31570	- NAVY RANGE FRONT LIGHT	30 20 04 N 87 18 59 W	<b>FI G</b> 2.5s	34		On skeleton tower on piles.	Visible all around, higher intensity on range line. Lighted throughout 24 hours.
			*	*	*		20/01

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

## SECTION II

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV LIGHT LIST, 2000

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
<b>PENSACOLA BAY (Chart 11383)</b>							
<b>Pensacola Bay</b>							
4175	- RANGE FRONT LIGHT	30 24 26 N 87 11 36 W	<b>FI W</b> 2.5s (Day) <b>FI G</b> 2.5s (Night)	15 18		On skeleton tower on piles.	DAY: Visible 2° each side of range line. NIGHT: Visible all around, higher intensity 2° each side of range line.
			*	*	*	*	* 20/01
4180	- RANGE REAR LIGHT 1,885 yards, 031.8° from front light.		<b>Iso W</b> 6s (Day) <b>Iso G</b> 6s (Night)	64 67		On skeleton tower on piles.	Visible 2° each side of range line.
			*	*		*	* 20/01
4950	MOBILE POINT RANGE FRONT LIGHT	30 12 18 N 88 02 00 W	<b>F R</b>	28		KRW on skeleton tower on mud sills.	Visible 2° each side of range line.
			*		*		* 20/01
*4953	MOBILE POINT RANGE FRONT PASSING LIGHT		<b>FI W</b> 4s	29	3	On same structure as Mobile Point Range Front Light.	
							20/01
*5073	MOBILE MIDDLE GROUND RANGE FRONT PASSING LIGHT		<b>FI W</b> 6s	15	5	On same structure as Mobile Middle Ground Range Front Light.	Obscured on range line, visible elsewhere.
							20/01
5075	MOBILE MIDDLE GROUND RANGE REAR LIGHT 611 yards, 350° from front light.		<b>Iso G</b> 6s	45		KRW on skeleton tower on piles.	Visible 2° each side of range line.
			*	*	*		* 20/01
*5077	MOBILE MIDDLE GROUND RANGE REAR PASSING LIGHT		<b>FI W</b> 6s	17	5	On same structure as Mobile Middle Ground Range Rear Light.	Obscured on range line, visible elsewhere.
							20/01
<b>Mobile Channel</b>							
5105	- LOWER REACH OUTER RANGE FRONT LIGHT	30 14 06 N 88 02 30 W	<b>FI W</b> 2.5s (Day) <b>FI W</b> 2.5s (Night)	22 20		Platform on pile.	DAY: Visible on range line only. NIGHT: Visible all around, higher intensity on range line.
			*	*	*		* 20/01
5110	- LOWER REACH OUTER RANGE REAR LIGHT 2,099 yards, 187° from front light.		<b>Oc W</b> 4s (Day) <b>Oc W</b> 4s (Night)	82 80		Skeleton tower on piles.	
			*	*	*		* 20/01
*5113	- LOWER REACH OUTER RANGE REAR PASSING LIGHTS (2)		<b>FI W</b> 4s	23	5	On same structure as Mobile Channel Lower Reach Outer Range Rear Light.	
							20/01

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

**SECTION II**

CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
5230	- MIDDLE REACH OUTER RANGE FRONT LIGHT	30 25 42 N 88 00 42 W	<b>Q R</b>	25		KRW on skeleton tower on piles.	Visible 3° each side of range line.
			*	*	*		* 20/01
*5233	- MIDDLE REACH OUTER RANGE FRONT PASSING LIGHT		<b>FI W 4s</b>	12	5	On same structure as Mobile Channel Middle Reach Outer Range Front Light.	
							20/01
5235	- MIDDLE REACH OUTER RANGE REAR LIGHT 2,100 yards, 174.5° from front light.	30 24 42 N 88 00 36 W	<b>Oc R 4s</b>	67		KRW on skeleton tower on piles.	Visible 3° each side of range line.
			*	*	*		* 20/01
*5237	- MIDDLE REACH OUTER RANGE REAR PASSING LIGHT		<b>FI W 4s</b>	12	9	On same structure as Mobile Channel Middle Reach Outer Range Rear Light.	
							20/01
5260	- LOWER REACH RANGE FRONT LIGHT	30 26 24 N 88 00 44 W	<b>Q W</b>	27		KGR on skeleton tower on piles.	Visible all around; higher intensity 2° each side of range line.
			*	*	*		* 20/01
*5263	- LOWER REACH RANGE FRONT PASSING LIGHT		<b>FIR 2.5s</b>	12	3	On same structure as Mobile Channel Lower Reach Range Front Light.	
							20/01
5265	- LOWER REACH RANGE REAR LIGHT 2,197 yards, 007.2° from front light.		<b>Oc W 4s</b>	63		KGR on skeleton tower on piles.	Visible 2° each side of range line.
			*	*	*		* 20/01
*5267	- LOWER REACH RANGE REAR PASSING LIGHTS (2)		<b>FI W 4s</b>	12	6	On same structure as Mobile Channel Lower Reach Range Rear Light.	
							20/01
5415	- RANGE FRONT LIGHT	30 36 30 N 88 02 00 W	<b>Q G</b>	25		KRW on skeleton tower on piles.	For downbound traffic. Visible 2° each side of range line.
			*	*	*		* 20/01
*5417	- RANGE FRONT PASSING LIGHT		<b>FI W 4s</b>	27	3	On same structure as Mobile Channel Range Front Light.	
							20/01
10412	- Daybeacon 3	30 16 51 N 90 18 33 W		15		SG on pile.	Ra ref.
		*					20/01

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

## SECTION II

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV LIGHT LIST, 2000

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*13633 33187	ALGIERS POINT LIGHT 95	29 57 19 N 90 03 19 W	<b>Q G</b>	34	5	SG-SY on piles.	20/01
22983	- PIPELINE MARKER LIGHT A						<i>Remove from list.</i>  * 20/01
23195	- LIGHT 73	29 35 42 N 94 56 42 W	<b>FI G</b> 4s	17	4	SG on pile.	Ra ref.  * 20/01
23265	- LIGHT 3		<b>FI G</b> 2.5s	17	4	SG on pile.	Ra ref.  * 20/01
28460 40845	- RANGE F FRONT LIGHT	25 57 02 N 97 24 11 W	<b>FI W</b> 2.5s (Day) <b>FI G</b> 2.5s (Night)	44		KRW-I on skeleton tower.	Visible 2° each side of rangeline.  * 20/01
<b>Santa Rosa Sound Entrance</b>							
30745	- LIGHT 1	30 24 02 N 86 33 38 W	<b>FI G</b> 2.5s	17	6	SG-SY on dolphin.	Visible all around, higher intensity on bearing 245°. Ra ref.  * 20/01
<b>SANTA ROSA SOUND TO DAUPHIN ISLAND (Chart 11378)</b>							
31500	SANTA ROSA SOUND LIGHT 133	30 21 04 N 87 08 30 W	<b>FI G</b> 2.5s	17	3	SG-SY on pile.	Ra ref.  * 20/01
32005	- LIGHT 68		<b>FI R</b> 4s	17	3	TR-TY on pile.	Ra ref.  * 20/01
32045	- Daybeacon 76					TR-TY on pile.	Ra ref.  * 20/01
*33187 13633	ALGIERS POINT LIGHT 95	29 57 19 N 90 03 19 W	<b>Q G</b>	34	5	SG-SY on piles.	20/01
37480	- Daybeacon 78					TR-TY on pile.	Ra ref.  * 20/01
40480	- LIGHT 139 90 feet outside channel limit.	26 05 30 N 97 12 12 W	<b>FI G</b> 2.5s	17	3	SG-SY on dolphin.	Ra ref.  * 20/01
40845 28460	- RANGE F FRONT LIGHT	25 57 02 N 97 24 11 W	<b>FI W</b> 2.5s (Day) <b>FI G</b> 2.5s (Night)	44		KRW-I on skeleton tower.	Visible 2° each side of rangeline.  * 20/01

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

**SECTION II**

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
240 3835	<b>Morro Bay West Breakwater Light</b>	35 21 46 N 120 52 11 W	<b>FI W 4s</b>	36	12	White column.	Obscured from 176° to 207°. HORN: 1 blast ev 30s (3s bl). Operates continuously.
						*	20/01
680 9810	<i>Tillamook Bay Approach Lighted Whistle Buoy T</i>	45 34 18 N 123 59 39 W	<b>Mo (A) W</b>		5	Red and white stripes.	
		*			*		20/01
<b>APPROACHES TO STRAIT OF JUAN DE FUCA (Chart 18480)</b>							
740 16075	<i>Quillayute River Approach Lighted Whistle Buoy Q</i>	47 53 07 N 124 40 33 W	<b>Mo (A) W</b>		5	Red and white stripes.	
		*					20/01
750	<i>Umatilla Reef Lighted Whistle Buoy 2UR</i>	48 11 12 N 124 49 17 W	<b>FI R 2.5s</b>		4	Red.	
		*			*		20/01
3835 240	<b>Morro Bay West Breakwater Light</b>	35 21 46 N 120 52 11 W	<b>FI W 4s</b>	36	12	White column.	Obscured from 176° to 207°. HORN: 1 blast ev 30s (3s bl). Operates continuously.
						*	20/01
8680	<i>- Entrance Lighted Bell Buoy 4</i>	43 07 42 N 124 27 02 W	<b>FI R 6s</b>		3	Red.	
		*			*		20/01
8750	<i>- Entrance Lighted Buoy 2</i>	43 21 26 N 124 21 03 W	<b>FI R 4s</b>		3	Red.	
		*			*		20/01
8765	<i>Guano Rock Lighted Whistle Buoy 4</i>	43 21 13 N 124 20 22 W	<b>FI R 4s</b>		3	Red.	
		*			*		20/01
8780	<i>- Channel Lighted Buoy 5A</i>	43 21 17 N 124 19 36 W	<b>FI G 4s</b>		3	Green.	
		*			*		20/01
8831	<i>- Channel Lighted Buoy 10A</i>	43 22 12 N 124 18 28 W	<b>FI R 4s</b>		3	Red.	
						*	20/01
9785	<i>- Entrance Lighted Bell Buoy 2</i>	44 48 30 N 124 04 25 W	<b>FI R 4s</b>		3	Red.	Replaced by bell buoy from Oct. 1 to May 1.
		*			*		20/01

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

## SECTION II

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI LIGHT LIST, 2000

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
<b>TILLAMOOK BAY (Chart 18558)</b>							
<b>Tillamook Bay</b>							
9810 680	- Approach Lighted Whistle Buoy T	45 34 18 N 123 59 39 W	<b>Mo (A) W</b>		5	Red and white stripes.	
		*			*		20/01
<b>PACIFIC OCEAN TO HARRINGTON POINT (Chart 18521)</b>							
<b>Miller Sands</b>							
10205	- Channel Lighted Buoy 2 75 yards outside channel limit.	46 14 59 N 123 40 50 W	<b>Q R</b>		3	Red.	
					*		20/01
10225	- Channel Lighted Buoy 10	46 15 28 N 123 38 56 W	<b>Q R</b>		3	Red.	
					*		20/01
10325	- Channel Lighted Buoy 28	46 16 14 N 123 29 57 W	<b>Q R</b>		3	Red.	
					*		20/01
10345	- Channel Lighted Buoy 32	46 15 59 N 123 28 02 W	<b>Q R</b>		3	Red.	
		*			*		20/01
10370	Multnomah Slough Lighted Buoy 36	46 14 45 N 123 26 22 W	<b>FI R 2.5s</b>		3	Red.	
		*			*		20/01
10375	Steamboat Slough Lighted Buoy 37	46 14 40 N 123 25 54 W	<b>FI G 4s</b>		4	Green.	
		*			*		20/01
10525	- Channel Lighted Buoy 68	46 08 39 N 123 17 24 W	<b>FI R 2.5s</b>		4	Red.	
		*			*		20/01
10575	- Channel Lighted Buoy 73	46 09 44 N 123 14 33 W	<b>FI G 4s</b>		4	Green.	
		*					20/01
10655	Crims Island Channel Lighted Buoy 86	46 11 09 N 123 07 42 W	<b>Q R</b>		3	Red.	
		*			*		20/01
10735	- Channel Lighted Buoy 10	46 09 16 N 123 03 30 W	<b>Q R</b>		3	Red.	
		*			*		20/01

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

**SECTION II**

**CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI LIGHT LIST, 2000**

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
11073	- Turn Lighted Buoy 1	45 51 08 N 122 46 58 W	<b>FI G</b> 4s		4	Green.	
		*					20/01
11243	Hayden Island Anchorage Lighted Buoy A	45 38 39 N 122 44 32 W	<b>FI Y</b> 6s			Yellow.	Private aid.
		*					20/01
15565	- Entrance Lighted Gong Buoy 5	46 54 50 N 124 12 35 W	<b>FI G</b> 4s		3	Green.	
							20/01
15700	- North Channel Lighted Bell Buoy 26	46 56 13 N 124 00 29 W	<b>FI R</b> 2.5s		4	Red.	
		*					20/01
15715	- NORTH CHANNEL RANGE C FRONT LIGHT	46 57 55 N 123 58 23 W	<b>Q W</b>	22		KRB on pile structure.	Visible all around; higher intensity on rangeline. Ra ref.
		*		*			20/01
15720	- NORTH CHANNEL RANGE C REAR LIGHT 900 yards, 043° from front light.		<b>Iso W</b> 6s	40		KRB on pile structure.	Visible 4° each side of rangeline. Ra ref.
				*			20/01

**APPROACHES TO STRAIT OF JUAN DE FUCA (Chart 18480)**

**Quillayute River**

16075 740	- Approach Lighted Whistle Buoy Q	47 53 07 N 124 40 33 W	<b>Mo (A) W</b>		5	Red and white stripes.	
		*					20/01

**CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII LIGHT LIST, 2001**

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
3732	CONNEAUT HARBOR NORTH LIGHT 2		<b>FI R</b> 3s	19 6		TR on post.	Maintained from May 1 to Nov. 1. Private aid.
						*	20/01
4140	- East Basin Channel Lighted Buoy 12		<b>FI R</b> 6s		4	Red.	Replaced by nun from Dec. 7 to Apr. 14.
							* 20/01
4155	- East Basin Channel Lighted Buoy 14		<b>FI R</b> 4s		3	Red.	
							* 20/01
6280	- Lighted Buoy 45	41 41 57 N 83 27 27 W	<b>FI G</b> 4s		4	Green.	Replaced by can from Dec. 14 to Apr. 7.
		*					20/01

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

## SECTION II

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII LIGHT LIST, 2001

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*11255	- Lighted Buoy 6	44 15 55 N 83 27 10 W	FI R 4s		6	Red.	Maintained from Apr. 28 to Dec. 1.  20/01
<b>BEAVER BAY TO PIGEON POINT (Chart 14967)</b>							
16540	NOAA Lighted Weather Buoy 45006	47 19 06 N 89 51 56 W	FI (4) Y 20s 1s fl 1.5s ec. 1s fl 1.5s ec. 1s fl 1.5s ec. 1s fl 11.5s ec.			Yellow 6 meter boat hull.	Replaced by nun from Nov. 1 to Apr. 1.  20/01
*							
16850	NOAA Lighted Weather Buoy 45004	47 33 50 N 86 32 58 W	FI (4) Y 20s			Yellow disc-shaped hull with tripod mast.	Replaced by nun from Nov. 1 to Apr. 1.  20/01
*							
16880	NOAA Lighted Weather Buoy 45001	48 03 49 N 87 46 40 W	FI (4) Y 20s 1s fl 1.5s ec. 1s fl 1.5s ec. 1s fl 1.5s ec. 1s fl 11.5s ec.			Yellow disc-shaped hull.	Replaced by nun from Nov. 1 to Apr. 1.  20/01
*							
<b>*Add Heading and Note:</b>							
<b>*South Bay Marina</b>							
*Lights maintained from Apr. 1 to Nov. 30.							
*22271	- EAST BREAKWATER LIGHT	44 32 23 N 87 59 51 W	FI W 6s	11 3		On pile.	Private aid.  20/01
*22271.1	- EAST MIDDLE BREAKWATER LIGHT	44 32 24 N 87 59 54 W	FI W 6s	11 3		On pile.	Private aid.  20/01
*22271.2	- WEST MIDDLE BREAKWATER LIGHT	44 32 25 N 87 59 58 W	FI W 6s	11 3		On pile.	Private aid.  20/01
*22271.3	- WEST BREAKWATER LIGHT	44 32 23 N 88 00 02 W	FI W 6s	11 3		On pile.	Private aid.  20/01

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.