

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME I LIGHT LIST, 2001							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
15805	- LIGHT 4	41 31 12 N 70 40 54 W	FI R 2.5s	28	4	TR on skeleton tower.	
		*					25/02
15807	- Buoy 4A	41 31 13 N 70 40 52 W				Red nun.	
		*					25/02
*16502	- Buoy 8A					Red nun.	Maintained from May 1 to Oct. 16. Private aid.
							25/02
Burlington Bay							
39615	- Breakwater North Light	44 28 48 N 73 13 48 W	FI W 2.5s	35	15	NW on skeleton tower with concrete base worded DANGER BREAKWATER.	Maintained from May 1 to Nov. 1. HORN: 1 blast ev 15s (2s bl).
							* 25/02

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2002							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
2310	- RANGE REAR LIGHT 1,037 yards, 247.7° from front light.		FG	65		On skeleton tower.	Visible all around; higher intensity on rangeline. Lighted throughout 24 hours.
	*					*	25/02
3530	HORSESHOE RANGE FRONT LIGHT	39 52 41 N 75 08 45 W	QR	10		KRW on skeleton tower.	Higher intensity on rangeline.
		*		*			25/02
3535	HORSESHOE RANGE REAR LIGHT 616 yards, 206° from front light.		Oc R 4s	25		KRW on skeleton tower.	Higher intensity on rangeline.
	*			*		*	25/02
3915	NESHAMINY MARINA JETTY LIGHT N	40 04 24 N 74 54 23 W	FI W 4s	32	5	NR on pile.	
		*					25/02
4375	- SOUTH JETTY LIGHT	38 36 28 N 75 03 33 W	FI G 4s	30	5	SG on skeleton tower.	
		*				*	25/02
4760	- LIGHT 12		FI R 2.5s	15	3	TR on multi-pile structure.	
					*	*	25/02
4775	- Junction Lighted Buoy OC	38 19 36 N 75 05 35 W	FI R (2+1) 6s		3	Red and green bands.	
		*					25/02

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2002

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
4790	- LIGHT 3	38 20 23 N 75 05 14 W	FI G 2.5s	15	3	SG on multi-pile structure.	
		*				*	25/02
4830	- Daybeacon 5	38 20 40 N 75 05 28 W				SG on pile.	
		*					25/02
4835	- LIGHT 6	38 21 01 N 75 05 29 W	FI R 4s	15	3	TR on multi-pile structure.	Light equipment removed when endangered by ice.
		*			*	*	25/02
4855	- LIGHT 9	38 21 31 N 75 05 18 W	FI G 4s	15	4	SG on multi-pile structure.	Light equipment removed when endangered by ice.
		*			*	*	25/02
4870	- LIGHT 13	38 22 02 N 75 05 25 W	FI G 2.5s	15	3	SG on pile.	Light equipment removed when endangered by ice.
		*					25/02
5010	- LIGHT 4	38 19 04 N 75 06 29 W	FI R 4s	15	3	TR on pile.	
		*		*			25/02
5020	- CHANNEL LIGHT 8		FI R 4s	15	3	TR on multi-pile structure.	Light equipment removed from Dec. 1 to Mar. 15.
						*	25/02
5055	- CHANNEL LIGHT 13		FI G 4s	15	4	SG on multi-pile structure.	
				*		*	* 25/02
5065	- CHANNEL LIGHT 15		FI G 4s	15	4	SG on multi-pile structure.	Light equipment removed when endangered by ice.
				*		*	25/02
5080	- CHANNEL LIGHT 19		FI G 4s	15	4	SG on multi-pile structure.	Light equipment removed from Dec. 1 to Mar. 15.
				*	*	*	25/02
5100	- CHANNEL LIGHT 25		FI G 4s	15	4	SG on multi-pile structure.	Light equipment removed from Dec. 1 to Mar. 15.
				*	*	*	25/02
5110	- Channel Daybeacon 27A	38 12 50 N 75 10 49 W				SG on pile.	
		*					25/02
5135	- CHANNEL LIGHT 35		FI G 4s	15	4	SG on pile.	Light equipment removed when endangered by ice.
				*			25/02

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2002							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
5145	- CHANNEL LIGHT 39		FI G 4s	15	4	SG on pile.	Light equipment removed when endangered by ice.
				*	*		25/02
	Chincoteague Bay						
5150	PUBLIC LANDING LIGHT 1		FI G 2.5s	15	3	SG on multi-pile structure.	Light equipment removed from Dec. 1 to Mar. 15.
						*	25/02
5155	TANHOUSE CREEK ENTRANCE LIGHT 2		FI R 2.5s	15	3	TR on pile.	
				*	*		25/02
5225	JOHNSON BAY ENTRANCE LIGHT 1	38 04 00 N 75 19 47 W	FI G 4s	15	4	SG on pile.	Light equipment removed from Dec. 1 to Mar. 15.
		*		*	*		25/02
5230	JOHNSON BAY ENTRANCE LIGHT 3	38 04 27 N 75 21 29 W	FI G 4s	15	4	SG on multi-pile structure.	Light equipment removed from Dec. 1 to Mar. 15.
		*		*		*	25/02
	George Island						
5245	- LANDING CHANNEL LIGHT 1	38 01 49 N 75 20 42 W	FI G 4s	15	4	SG on pile.	Light equipment removed from Dec. 1 to Mar. 15.
		*			*		25/02
5305	- Lighted Buoy 8	37 52 24 N 75 24 54 W	FI R 2.5s		3	Red.	
					*		25/02
5325	- Lighted Buoy 12	37 52 54 N 75 23 54 W	FI R 4s		3	Red.	
	*			*	*	*	25/02
5335	- LIGHT 14	37 53 34 N 75 23 52 W	FI R 2.5s	15	3	TR on multi-pile structure.	
		*			*	*	25/02
5860	Parker Creek Channel Buoy 4					Red nun.	
	*					*	25/02
8340	LOVE POINT LIGHT On shoal east side of bay.	39 03 25 N 76 16 59 W	FI W 6s (R sector)	35	W 9 R 7	NR on skeleton tower.	Red from 017° to 061° covers shoal off Love Point.
		*					25/02
8575	POOLES ISLAND BAR LIGHT	39 15 42 N 76 16 41 W	FI W 2.5s (R sector)	27	W 6 R 4	Black skeleton tower on cylindrical base.	Red from 058° to 225°.
		*					25/02

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2002

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
8680	POOLES ISLAND EAST RANGE FRONT LIGHT	39 16 42 N 76 16 05 W	Q W	19		KWB on skeleton tower.	
		*					25/02
9553.5	- North Channel Buoy 8	36 55 21 N 76 19 54 W				Red nun.	
		*					25/02
Rappahannock River							
15285	- LIGHT 8		FI R 2.5s	15	4	TR on multi-pile structure.	
	*		*	*		*	25/02
17765	- LIGHT 6		FI R 4s	15	3	TR on multi-pile structure.	
				*	*		25/02
26420	- LIGHT 3		FI G 4s	15	4	SG on multi-pile structure.	
					*		25/02
26425	- LIGHT 4		FI R 4s	15	4	TR on multi-pile structure.	
					*		25/02
26430	- LIGHT 5		Q G	15	4	SG on pile.	
					*		25/02
26435	- LIGHT 6		Q R	15	4	TR on pile.	
					*		25/02
26440	- LIGHT 8		FI R 2.5s	15	4	TR on pile.	
					*		25/02
31380 37055	- ENTRANCE LIGHT AS	36 03 44 N 75 56 08 W	Mo (A) W	16	7	MR-I on multipile structure.	Higher intensity beam up and down channel.
	*						25/02
33400 38245	- LIGHT 1	35 09 48 N 76 32 01 W	FI G 4s	15	3	SG-TY on pile.	
	*						25/02
33405 38250	- LIGHT 3	35 10 48 N 76 33 31 W	FI G 4s	15	5	SG-TY on pile.	Higher intensity beam down channel.
	*	*			*		25/02
37055 31380	- ENTRANCE LIGHT AS	36 03 44 N 75 56 08 W	Mo (A) W	16	7	MR-I on multipile structure.	Higher intensity beam up and down channel.
	*						25/02
Bay River							
38245 33400	- LIGHT 1	35 09 48 N 76 32 01 W	FI G 4s	14	3	SG-TY on pile.	Higher intensity beam down channel.
	*						25/02

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2002

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
38250 33405	- LIGHT 3	35 10 48 N 76 33 31 W	FI G 4s	15	5	SG-TY on pile.	
*		*			*		25/02

CORRECTIONS TO C. G. LIGHT LIST, VOLUME III LIGHT LIST, 2001

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
1825	- Buoy 17					Green can.	
	*					*	25/02
21775	- Daybeacon 5						Remove from list.
							* 25/02
21825	- Daybeacon 7 Marks large boulder.						Remove from list.
							* 25/02
*21827	- Daybeacon 8					TR on pile.	
							25/02
*21829	- Daybeacon 9					SG on pile.	
							25/02
*56137	- Daybeacon 74					TR-TY on pile.	
							25/02

CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV LIGHT LIST, 2001

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
1405	NOAA Lighted Buoy 42002 (ODAS)	25 10 48 N 93 24 30 W	FI (4) Y 20s	33	5	Yellow disc buoy with mast.	Maintained by National Oceanic and Atmospheric Administration.
		*					25/02
	*Delete Heading: *Marine Scientific Marine Research						
5880	- LIGHT A						Remove from list.
							* 25/02
5885	- LIGHT B						Remove from list.
							* 25/02
5890	- LIGHT C						Remove from list.
							* 25/02
11475	BRETON ISLAND LIGHT						Remove from list.
							* 25/02

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV LIGHT LIST, 2001

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
TIMBALIER AND TERREBONNE BAYS (Chart 11357)							
Cat Island Pass							
17110 665	- Entrance Lighted Whistle Buoy CI	29 00 13 N 90 33 55 W	Mo (A) W		6	Red and white stripes with red spherical topmark.	
		*					25/02
17115	- Lighted Buoy 1	29 01 09 N 90 34 05 W	FI G 6s		4	Green.	
		*					25/02
37410	- Buoy 66						<i>Remove from list.</i>
						*	25/02
Corpus Christi Bay							
37415	- Buoy 66	27 48 54 N 97 11 42 W				Red nun with yellow triangle.	
		*					25/02
37420	- OBSTRUCTION LIGHT 66A Marks submerged pipe.	27 48 42 N 97 11 48 W	Q R	17	3	TR-TY on pile.	
		*					25/02

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI LIGHT LIST, 2001

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
155	<i>San Pedro Channel Traffic Lane Lighted Buoy W</i>	33 39 06 N 118 17 36 W	FI Y 6s		4	Yellow.	BELL .
		*					* 25/02
265	Piedras Blancas Light	35 39 56 N 121 17 04 W	FI W 10s	142	21	White conical tower with a flat top.	Private aid.
					*		* 25/02
482	<i>NOAA Enviromental Lighted Buoy EB 46030</i>						<i>Remove from list.</i>
							* 25/02
635	Heceta Head Light	44 08 15 N 124 07 42 W	FI W 10s	205	28	White conical tower. 56	Lighted throughout 24 hours. Private aid.
		*			*		25/02
690	<i>Columbia River Approach Lighted Horn Buoy CR</i>	46 11 05 N 124 11 03 W	Mo (A) W FI W 2.5s		6	Red and white stripes.	High intensity flash tube FI W 2.5s. RACON: M (--) HORN: 1 blast ev 30s (3s bl).
		*					25/02

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI LIGHT LIST, 2001							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
2985	- Lighted Mooring Buoy LB1						Remove from list. * 25/02
2990	- Lighted Mooring Buoy LB2						Remove from list. * 25/02
2995	- Lighted Mooring Buoy LB3						Remove from list. * 25/02
3000	- Lighted Mooring Buoy LB4						Remove from list. * 25/02
3005	- Lighted Mooring Buoy LB5						Remove from list. * 25/02
3215	- Lighted Mooring Buoy C						Remove from list. * 25/02
8705	- Entrance Small Boat Warning Sign	43 07 15 N 124 25 03 W	Q Y (2)	29		NW worded ROUGH BAR.	Lights flashing when seas exceed four feet in height, lights extinguished for lesser bar conditions, but with no guarantee that bar is safe. Maintained from May 15 to Oct. 1. * 25/02
8710	- Rock Buoy 11	43 07 20 N 124 25 06 W				Green can.	Maintained from May 15 to Oct. 1. * 25/02
8725	- Buoy 15	43 07 20 N 124 24 42 W				Green can.	Maintained from May 15 to Oct. 1. * 25/02
9245	- SOUTH JETTY LIGHT 2A	43 39 59 N 124 13 10 W	F I R 2.5s	15	3	TR on skeleton tower.	HORN: 1 blast ev 15s (2s bl). Light and horn maintained from May 20 to Sept. 30. Ra ref. * 25/02
9605	- SOUTH JETTY LIGHT 4	44 36 34 N 124 04 46 W	F I R 2.5s	20	4	Red pile structure.	Due to weather conditions, the dayboards have been permanently removed from this aid. HORN: 1 blast ev 15s (2s bl). Operates continuously. Light and fog signal maintained from May 20 to Oct. 1. * 25/02

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI LIGHT LIST, 2001

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
Puget Island							
10385	- RANGE FRONT LIGHT	46 13 40 N 123 25 18 W	Q W	25		KRB on pile structure.	Visible 4° each side of rangeline.
		*		*			25/02
*12930.91	- Channel Approach Buoy H	46 05 36 N 118 55 36 W				Yellow can.	Private aid.
							25/02
*12930.92	- Channel Approach Buoy 5	46 05 47 N 118 55 30 W				Green can.	Private aid.
							25/02
*12930.93	- Channel Approach Buoy 7	46 05 52 N 118 55 28 W				Green can.	Private aid.
							25/02
*12930.94	- Channel Approach Buoy 9	46 05 57 N 118 55 25 W				Green can.	Private aid.
							25/02
*Add Heading: *Meldrum Bar							
*15077.1	- Daybeacon 1	45 22 47 N 122 37 07 W				SG on piling.	Private aid.
							25/02
*15077.2	- Daybeacon 2	45 22 46 N 122 37 08 W				TR on piling.	Private aid.
							25/02
*15077.3	- Daybeacon 3	45 22 46 N 122 37 06 W				SG on piling.	Private aid.
							25/02
*15077.4	- Daybeacon 4	45 22 42 N 122 37 04 W				TR on piling.	Private aid.
							25/02
*15077.5	- Daybeacon 5	45 22 41 N 122 37 01 W				SG on piling.	Private aid.
							25/02
*15077.6	- Daybeacon 6	45 22 39 N 122 37 00 W				TR on piling.	Private aid.
							25/02
15571	- Entrance Lighted Whistle Buoy 8	46 54 29 N 124 10 57 W	Q R		3	Red.	High intensity flashtube FI R 2.5s.
		*					* 25/02
15745	- NORTH CHANNEL RANGE E FRONT LIGHT	46 58 13 N 123 55 06 W	Q G	20		KRB on pile structure.	Visible 4° each side of rangeline.
		*					25/02

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI LIGHT LIST, 2001							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
15785	- NORTH CHANNEL RANGE F FRONT LIGHT	46 58 11 N 123 55 44 W	Q W	27		KRB on pile structure.	Visible all around; higher intensity on rangeline.
		*					25/02
15790	- NORTH CHANNEL RANGE F REAR LIGHT 370 yards, 273.9° from front light.		Iso W 6s	35		KRB on pile structure.	Visible 5.5° each side of rangeline.
							* 25/02
*17977	Liberty Bay Marina No Wake Buoy	47 43 20 N 122 38 47 W				White can with orange bands and diamond worded NO WAKE.	Private aid.
							25/02
26395	RACE POINT RANGE FRONT LIGHT						<i>Remove from list.</i>
							* 25/02
26400	RACE POINT RANGE REAR LIGHT 1,100 yards, 058° from front light.						<i>Remove from list.</i>
							* 25/02

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII LIGHT LIST, 2002							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
3345	Niagara Falls Safety Buoy A Marks safety zone above Niagara Falls.	43 04 06 N 79 01 07 W				White can with orange bands and danger symbol.	Maintained from May 1 to Oct. 25.
		*					25/02
3359.1	- Safety Buoy 1 Marks safety zone above Niagra Falls. (C)	42 03 46 N 79 02 32 W				White can with orange bands and danger symbols.	Maintained from May 1 to Oct. 7.
		*					25/02
19800	- Harbor Breakwater South End Light	41 43 34 N 87 29 36 W	Al WR 10s 0.2s W fl 4.8s ec. 0.2s R fl 4.8s ec.	50 15	W 15 R 12	White square skeleton tower with red band. Lower half open.	HORN: 1 blast ev 15s (2s bl). Operates from Apr. to Dec.
					*		25/02
19931	THIRTY-FIRST STREET JETTY DANGER LIGHTED BUOY A	41 50 23 N 87 36 18 W	FI W 2s			White with orange bands and diamond worded DANGER BREAKWATER.	Maintained from Apr. 15 to Oct. 31. Private aid.
		*	*				25/02
	*Delete Heading: *CHICAGO HARBOR (Chart 14928)						
19932	THIRTY-FIRST STREET JETTY DANGER LIGHTED BUOY B	41 50 23 N 87 36 21 W	FI W 2s			White with orange bands and diamond worded DANGER BREAKWATER.	Maintained from Apr. 15 to Oct. 31. Private aid.
							* 25/02

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII LIGHT LIST, 2002

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*Delete Heading: *CHICAGO HARBOR (Chart 14928)							
19933	THIRTY-FIRST STREET JETTY DANGER LIGHTED BUOY C	41 50 24 N 87 36 23 W	FI W 2s			White with orange bands and diamond worded DANGER BREAKWATER.	Maintained from Apr. 15 to Oct. 31. Private aid.
			*				25/02
19990	- SOUTH BREAKWATER NORTHEND LIGHT 1	41 52 29 N 87 36 36 W	FI G 2.5s	35 11	4	SG on post.	
		*					25/02
20010	- NAVY PIER SOUTH LIGHT		Iso W 4s	30 9		On skeleton tower.	Maintained from Apr. 1 to Dec. 1. Private aid.
	*		*				25/02
20012	- NAVY PIER NORTH LIGHT		Iso W 4s	30 9		On skeleton tower.	Maintained from Apr. 1 to Dec. 1. Private aid.
	*		*				25/02
20015	- FILTRATION PLANT LIGHT B		FI W 4s	15 5		On dolphin.	Maintained from Mar. 15 to Dec. 15. Private aid.
			*	*			25/02
20020	- FILTRATION PLANT LIGHT A		FI W 4s	10 3			Maintained from Mar. 15 to Dec. 15. Private aid.
			*	*			25/02
20035	- OAK STREET BREAKWATER SOUTHWEST END LIGHT 3	41 54 05 N 87 37 02 W	FI G 2.5s	26 8	5	SG on post.	
		*					25/02
20335	- BREAKWATER LIGHT		FI (2) W 5s 0.4s fl 0.6s ec. 0.4s fl 3.6s ec.	32 10	6	White cylindrical tower with black band.	
						*	25/02
20605	Wind Point Light Marks shoal.	42 46 52 N 87 45 30 W	FI W 20s	111 34	28	White conical tower connected to dwelling. 108	
	*	*				*	25/02
21010	- Lighted Buoy 2						Remove from list.
							* 25/02
*21014	Oconto Harbor Lighted Bell Buoy	44 53 00 N 87 46 00 W	FI R 4s		4	Red.	Maintained from May 01 to Nov. 14.
							25/02

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII LIGHT LIST, 2002

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
21620	<i>Ford River Shoal Lighted Buoy 5</i> Marks southeast side of shoal.	45 38 33 N 87 03 40 W	FI G 4s		4	Green.	Maintained from Apr. 28 to Nov. 21.
		*					25/02
LITTLE BAY DE NOC (Chart 14915)							
Little Bay De Noc							
21630	- <i>Lighted Buoy 8</i> Marks shoal.	45 43 46 N 87 01 31 W	FI R 4s		4	Red.	Maintained from Apr. 28 to Dec. 1.
		*					25/02
21645	Escanaba Buoy 1 Marks north side of obstruction.	45 44 50 N 87 02 39 W				Green can.	
		*					25/02
21685	- <i>Lighted Traffic Buoy</i>	45 48 15 N 87 02 23 W	Mo (A) W		6	Red and white stripes.	Maintained from Apr. 28 to Nov. 21.
		*					25/02
21745	Kipling Channel Buoy 8	45 51 51 N 86 59 59 W				Red nun.	Maintained from May 15 to Oct. 15.
		*					25/02
22130	Green Bay Harbor Entrance Light	44 39 12 N 87 54 06 W	Oc R 4s	72 22	12	White conical tower on cylindrical base.	Standby light of reduced intensity. Lighted throughout 24 hours. HORN: 1 blast ev 15s (2s bl). Maintained from Apr. 1 to Nov. 1.
							* 25/02
*Add Heading: *Molokai Island							
*22188	- <i>Entrance Lighted Buoy 15A</i>		FI G 4s			Green.	Maintained from Apr. 28 to Dec. 1.
							25/02
*22189	- <i>Entrance Lighted Buoy 16A</i>		FI R 4s			Green.	Maintained from Apr. 28 to Dec. 1.
							25/02
*Add Headings: *Green Bay Harbor *Green Bay Harbor Entrance Channel							
22200	- <i>Lighted Buoy 17</i>	44 34 54 N 87 58 36 W	Q G		4	Green.	Replaced by can from Dec. 1 to Apr. 28.
							25/02

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.