

## SECTION II

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME I LIGHT LIST, 2002

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
<b>NEW BRUNSWICK - GRAND MANAN CHANNEL NORTHERN PART (Chart 13394)</b>							
840	West Quoddy Head Bell Buoy WQ	44 49 25 N 66 56 41 W				Red and white stripes with red spherical topmark.	
		*					40/02
<b>FRENCHMAN BAY AND MOUNT DESERT ISLAND (Chart 13318)</b>							
<b>Winter Harbor</b>							
1915	<i>Mark Island Junction</i> <i>Lighted Gong Buoy MI</i>	44 21 29 N 68 05 07 W	<b>FI (2+1) G 6s</b>			4 Green and red bands.	
		*					40/02
2570	- <i>Lighted Bell Buoy 8</i>	44 11 12 N 68 28 53 W	<b>FIR 4s</b>			4 Red.	Replaced by nun when endangered by ice.
		*					40/02
<b>BLUE HILL BAY (Chart 13316)</b>							
<b>Pond Island Passage</b>							
2575	- Buoy 1 Northeasterly of shoal.	44 14 20 N 68 28 45 W				Green can.	
		*					40/02
3155	York Island Rock Buoy 1	44 04 08 N 68 34 47 W				Green can.	
		*					40/02
3255	Mackerel Ledge Buoy 5 North of northerly ledge.	43 52 06 N 68 51 41 W				Green can.	
		*					40/02
3355	Rock T Buoy 6 Northwest of rock.	44 02 20 N 68 40 16 W				Red nun.	
		*					40/02
3505	Green Ledge Bell Buoy 2	44 17 13 N 68 50 00 W				Red.	Removed when endangered by ice.
		*					40/02
3680	- Buoy 28	44 45 18 N 68 48 47 W				Red nun.	Replaced by nun when endangered by ice from Dec. 1 to Apr. 1.
		*					40/02
<b>Laireys Narrows</b>							
3820	- <i>East Entrance</i> <i>Lighted Buoy 1</i> East of ledge.	44 03 58 N 68 53 39 W	<b>FIG 2.5s</b>			4 Green.	
		*					40/02
3825	- <i>Rocks Lighted</i> <i>Buoy 2A</i>	44 04 06 N 68 54 13 W	<b>FIR 4s</b>			4 Red.	
		*					40/02

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

## SECTION II

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME I LIGHT LIST, 2002

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
<b>Fox Island Thorofare</b>							
3860	- Buoy 2A	44 07 55 N 68 46 41 W				Red nun.	
		*					40/02
3995	- Buoy 27 North of 14-foot spot.	44 05 17 N 68 56 55 W				Green can.	
		*					40/02
4000	- <i>Lighted Bell Buoy FT</i>	44 05 18 N 68 57 17 W	<b>Mo (A) W</b>		6	Red and white stripes.	
		*					40/02
<b>Inner Bay Ledges</b>							
4090	- Buoy 4 At south end of ledges.	44 04 21 N 68 57 20 W				Red nun.	
		*					40/02
4235	- Town Channel Buoy 1	44 06 12 N 69 06 01 W				Green can.	
		*					40/02
4275	Rockport Outer Bell Buoy RO	44 09 29 N 69 03 12 W				Red and white stripes.	
		*					40/02
4315	- Entrance Bell Buoy 2	44 12 00 N 69 02 25 W				Red.	
		*					40/02
4360	<i>Ensign Island Lighted Bell Buoy 1</i>	44 13 32 N 68 57 50 W	<b>FI G 4s</b>		4	Green.	
		*					40/02
<b>West Penobscot Bay</b>							
4452	<i>Moose Point Isolated Danger Lighted Buoy DMP</i>	44 24 51 N 68 55 05 W	<b>FI (2) W 5s</b>			Black over red with (2) black spherical topmarks.	
		*					40/02
4465	<i>Mack Point Channel Lighted Bell Buoy 5</i>	44 26 35 N 68 54 08 W	<b>FI G 4s</b>		4	Green.	
		*					40/02
<b>Stockton Harbor</b>							
4485	- <i>Entrance Shoal Lighted Gong Buoy 1</i> South of 23-foot spot.	44 25 04 N 68 52 27 W	<b>FI G 4s</b>		4	Green.	Replaced by can when endangered by ice.
		*					40/02

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

## SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME I LIGHT LIST, 2002							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
<b>Wheeler Bay</b>							
4705	- Buoy 1 South of Norton Island Ledges	43 58 12 N 69 09 21 W				Green can.	
		*					40/02
4915	- LIGHT 21	44 04 11 N 69 10 47 W	FI W 6s	14	5	On skeleton tower.	
		*					40/02
4980	FRANKLIN ISLAND LIGHT	43 53 32 N 69 22 29 W	FI W 6s	57	8	White tower.	Obscured by trees from 253° to 352°.
		*					40/02
5280	Little River Daybeacon 1	43 49 17 N 69 34 56 W				Green cylinder on monopile.	
		*				*	40/02
<b>Christmas Cove</b>							
5300	Foster Point Shoal Buoy FP Marks 8 foot spot	43 50 28 N 69 34 00 W				Red nun with green bands.	
		*					40/02
5705	- LIGHT 5	43 50 56 N 69 43 15 W	FI G 2.5s	16	5	SG on skeleton tower on caisson.	Higher intensity beam up Knubble Bay and down Goose Rock Passage.
		*					40/02
5800	Merrill Ledge Daybeacon 22A On south point of ledge.					TR on spindle.	
						*	40/02
5830	- Daybeacon 3					SG on spindle.	
						*	40/02
6120	PETTIS ROCKS LIGHT 23 Off south end of rocks.	43 49 49 N 69 47 57 W	FI G 2.5s	20	4	SG on skeleton tower.	
		*					40/02
6125	- LIGHT 25	43 50 12 N 69 47 51 W	FI G 4s	22	4	SG on skeleton tower, small white house.	Ra ref.
		*					40/02
6175	- Buoy 35						Remove from list.
							* 40/02
6275	- Daybeacon 26 On north end of Beef Rock.					TR on spindle.	Maintained from Apr. 1 to Oct. 15.
						*	40/02

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

## SECTION II

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME I LIGHT LIST, 2002

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
<b>CASCO BAY (Chart 13290)</b>							
<b>New Meadows River Approach</b>							
6440	FULLER ROCK LIGHT	43 41 42 N 69 50 00 W	FI W 4s	25	6	NR on white skeleton tower.	
				*			40/02
6535	Goudy Ledge Daybeacon South of ledge.					NR on pile.	
						*	40/02
6580	BIRCH POINT LIGHT 8	43 49 34 N 69 52 12 W	FI R 4s	25	5	TR on white structure with small white house.	Higher intensity beam downstream.
		*					40/02
6700	LITTLE MARK ISLAND MONUMENT LIGHT	43 42 33 N 70 01 53 W	FI W 4s	74	5	Black and white square stone pyramid.	
		*					40/02
6845	WHALEBOAT ISLAND LIGHT	43 44 32 N 70 03 41 W	FI W 6s	47	6	NR on white square skeleton tower.	
		*					40/02
7225	HOUSE ISLAND LIGHT 3	43 39 21 N 70 12 28 W	FI G 4s	20	3	SG on skeleton tower.	
		*					40/02
7295	Lower Basket Ledge Daybeacon 15	43 43 49 N 70 09 24 W				SG on iron spindle.	Ra ref.
		*					40/02
7350	York Ledge Daybeacon YL	43 43 30 N 70 12 01 W				SG on pile.	Maintained from May 15 to Oct. 15.
		*					40/02
7360	Clapboard Island North Ledge Daybeacon 18	43 43 25 N 70 11 28 W				TR on spindle.	
		*					40/02
7605	FORT SCAMMEL POINT LIGHT 2	43 38 57 N 70 12 50 W	FI R 4s	35	5	TR on tower.	Higher intensity beam up channel.
		*					40/02
7827	- Daybeacon 5A	43 38 15 N 70 16 47 W				SG on pile.	
		*					40/02
7960	Stage Island Daybeacon	43 27 24 N 70 20 59 W				Conical stone tower.	
		*					40/02

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

## SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME I LIGHT LIST, 2002							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
7975	Sharps Rock Daybeacon 4A	43 27 46 N 70 21 21 W				TR on spindle.	
		*					40/02
7990	- Daybeacon 5B	43 27 37 N 70 21 51 W				SG on spindle.	
		*					40/02
8015	Jordan Point Daybeacon 9	43 27 41 N 70 23 38 W				SG on spindle.	Maintained from Apr. 1 to Nov. 1.
		*					40/02
8050	Cow Island Ledge Daybeacon 17	43 29 18 N 70 26 58 W				SG on spindle.	
		*					40/02
8065	Phillip Rock Daybeacon 5					SG on on spindle.	
						*	40/02
8110	Folly Island Daybeacon On ledge.					NW on pile worded DANGER.	
						*	40/02
8120	Goat Island Daybeacon 8 On ledge.					TR on pile.	
						*	40/02
8155	Fishing Rock Daybeacon F					NB on pile.	Ra ref.
						*	40/02
8165	- BREAKWATER LIGHT 6	43 20 46 N 70 28 34 W	<b>Iso R 6s</b>	25	5	TR on spindle.	
		*					40/02
8195	- Daybeacon 12					TR on spindle.	
						*	40/02
8210	- NORTH JETTY LIGHT 2	43 19 02 N 70 33 11 W	<b>FI R 4s</b>	29	5	TR on skeleton tower.	
		*					40/02
8248	- Daybeacon 4	43 14 06 N 70 35 15 W				Red cylinder with retro band.	
		*					40/02
8345	CLARK ISLAND LIGHT 8	43 04 34 N 70 43 27 W	<b>FI R 2.5s</b>	20	4	TR on sectional spindle.	
		*					40/02
8880	- LIGHT 4	42 59 59 N 70 44 40 W	<b>FI R 6s</b>	24	5	TR on skeleton tower.	Higher intensity beam between 297.5° and 300.5°.
		*					40/02

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

## SECTION II

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME I LIGHT LIST, 2002

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
10070	Great Aquavitae Daybeacon					NR on spindle.	
						*	40/02
<b>Rams Horn Channel</b>							
10270	Monument Bar Daybeacon 1	42 32 23 N 70 52 24 W				SG on spindle on cribwork base.	
		*				*	40/02
10580	WHITE ROCKS LIGHT 7 125 feet outside channel limit.	42 25 34 N 70 57 14 W	<b>FIG 2.5s</b>	49	4	SG on multi-pile.	Higher intensity beam up and down channel.
		*				*	40/02
10585	BLACK ROCKS LIGHT 9	42 25 59 N 70 56 53 W	<b>FIG 6s</b>	49	9	SG on multi-pile.	Higher intensity beam up and down channel.
		*				*	40/02
10595	SANDY POINT LIGHT 11 75 feet outside channel limit.		<b>FIG 2.5s</b>	45	4	SG on multi-pile.	Higher intensity beam up and down channel.
						*	40/02
10615	BLACK MARSH CHANNEL LIGHT 15	42 26 54 N 70 56 31 W	<b>FIG 4s</b>	44	7	SG on multi-pile.	Higher intensity beam up and down channel.
		*				*	40/02
11519	- LIGHT 4P East of Sunken Ledge.	42 17 36 N 70 57 24 W	<b>FIR 46s</b>	26	4	TR on grey skeleton tower on pile structure.	
			*				40/02
11549	Sunken Ledge Daybeacon SL					NB on spindle.	
						*	40/02
14050	- EAST JETTY LIGHT 6	41 39 49 N 70 03 40 W	<b>FIR 4s</b>	20	6	TR on white skeleton tower.	
		*					40/02
*15134	Nantucket Sound CG Mooring Buoy	41 21 00 N 07 05 00 W				White Sphere with blue stripe.	
							40/02
<b>Madaket Harbor</b>							
<i>Aids maintained from June 15 to Nov. 15 unless otherwise noted.</i>							
15295	- Approach Lighted Bell Buoy 2	41 18 57 N 70 11 09 W	<b>FIR 2.5s</b>		4	Red.	Replaced by nun buoy from Nov. 15 to May 1.
		*					40/02
15485	- Ferry Slip Fog Signal						Remove from list.
							* 40/02

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

## SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME I LIGHT LIST, 2002							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
15770	Middle Ledge East Danger Buoy						<i>Remove from list.</i>
							* 40/02
15805	- LIGHT 4	41 31 13 N 70 40 51 W	F I R 2.5s	28	4	TR on skeleton tower.	
		*					40/02
	<b>East Side</b>						
16375	Great Sippewisset Rock Daybeacon	41 35 18 N 70 39 18 W				TR on spindle.	Maintained from May 15 to Oct. 15. Private aid.
						*	40/02
17355	- Channel Buoy 13	41 44 05 N 70 39 15 W				Green can.	
		*					40/02
	<b>Westport Harbor Approach</b>						
17425	Gooseberry Neck Buoy 2	41 28 45 N 71 01 42 W				Red nun.	
		*					40/02
17490	- Channel Lighted Buoy 14	41 30 34 N 71 05 37 W	F I R 2.5s		4	Red.	Replaced by nun when endangered by ice.
		*					40/02
17525	- Channel Buoy 26	41 31 01 N 71 05 07 W				Red nun.	
	*						40/02
	<b>Newport Harbor</b>						
17820	- Buoy 4	41 28 52 N 71 20 06 W				Red nun.	
		*					40/02
17860	Rose Island South Point Buoy 1	41 29 36 N 71 20 24 W				Green can.	
		*					40/02
17930	Seventeen-Foot Spot Buoy	41 30 25 N 71 20 08 W				Green can with red bands.	
		*					40/02
18010	Coddington Cove Buoy 2	41 32 00 N 71 18 56 W				Red nun.	
		*					40/02
	<b>Bristol Harbor</b>						
18165	Bristol Point Rock Buoy 2	41 38 28 N 71 15 57 W				Red nun.	
		*					40/02

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

## SECTION II

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME I LIGHT LIST, 2002

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
18185	Usher Rocks Buoy 3	41 39 32 N 71 17 21 W				Green can.	
		*					40/02
18255	Fork Rock Buoy	41 40 33 N 71 20 51 W				Red nun with green bands.	
		*					40/02
<b>Bullock Cove</b>							
18350	- Entrance Lighted Buoy 1	41 44 16 N 71 21 22 W	<b>FI G</b> 2.5s		4	Green.	Replaced by can when endangered by ice.
		*					40/02
18370	- Entrance Buoy 3	41 44 27 N 71 21 17 W				Green can.	
		*					40/02
18375	- Entrance Buoy 4	41 44 28 N 71 21 16 W				Red nun.	
		*					40/02
18385	- Entrance Buoy 6	41 44 33 N 71 21 15 W				Red nun.	
		*					40/02
18490	- Channel Lighted Buoy 6	41 45 34 N 71 23 10 W	<b>FI R</b> 4s		3	Red.	Replaced by nun when endangered by ice.
		*					40/02
<b>Fields Point Channel</b>							
18510	- Buoy 1	41 46 10 N 71 22 51 W				Green can.	
		*					40/02
<b>Mount Hope Bay</b>							
18785	- Bridge Fog Signal						Private aid. SIREN: 2s blast ev 15s.
							* 40/02
19480	<b>Block Island North Light</b>	41 13 42 N 71 34 36 W	<b>FI W</b> 5s	58	13	Brown tower on grey dwelling. 52	
						*	40/02
19720	- Breakwater Light 3	41 10 36 N 71 33 18 W	<b>FI G</b>	27	11	SG on white skeleton tower on base.	HORN: 2 blasts ev 30s (2s bl-2s si-2s bl-24s si).
						*	40/02
19725	- BREAKWATER OUTER BASIN LIGHT 8	41 10 24 N 71 33 18 W	<b>FI R</b> 2.5s	23	6	TR on skeleton tower.	
							* 40/02

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

## SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME I LIGHT LIST, 2002							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
20915	- South Branch Daybeacon 2						<i>Remove from list.</i>
							* 40/02
20920	- South Branch Daybeacon 3						<i>Remove from list.</i>
							* 40/02
20930	- Buoy 5						<i>Remove from list.</i>
							* 40/02
20935	- Buoy 8						<i>Remove from list.</i>
							* 40/02
20940	- Buoy 9						<i>Remove from list.</i>
							* 40/02
20945	- Buoy 11						<i>Remove from list.</i>
							* 40/02
20950	- North Junction Buoy						<i>Remove from list.</i>
							* 40/02
20955	- North Branch Buoy 2						<i>Remove from list.</i>
							* 40/02
20960	- North Branch Buoy 4						<i>Remove from list.</i>
							* 40/02
20965	- North Branch Buoy 5						<i>Remove from list.</i>
							* 40/02
21480	GANGWAY ROCK LIGHT 27A Near end of shoal.	40 51 29 N 73 44 46 W	<b>FI G</b> 6s	40	6	SG on skeleton tower.	
		*					40/02
21500	HART ISLAND LIGHT 46	40 50 42 N 73 46 04 W	<b>FI R</b> 4s	23	6	TR on skeleton tower, concrete base on rocks.	
		*					40/02
25965	GLEN ISLAND LIGHT 15	40 53 21 N 73 46 49 W	<b>FI G</b> 4s	20	5	SG on tower on concrete base.	
		*					40/02
26005	Cuban Ledge Daybeacon	40 50 30 N 73 48 14 W				NW on spindle worded DANGER ROCK.	
		*					40/02

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

## SECTION II

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME I LIGHT LIST, 2002

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
27110	BAR BEACH LIGHT 11	40 49 55 N 73 39 12 W	FI G 4s	26	4	SG on skeleton tower.	
		*					40/02
27245	NORTH BROTHER ISLAND NORTH LIGHT 9	40 48 09 N 73 53 55 W	FI G 4s	33	4	SG on tower.	
		*					40/02
27265	SOUTH BROTHER ISLAND LIGHT SB	40 47 52 N 73 53 53 W	FI W 2.5s	20	5	NG on skeleton tower.	
		*					40/02
31385	- Buoy 2					Red nun.	Maintained year round.
							* 40/02
31390	- Buoy 3					Green can.	Maintained year round.
							* 40/02
31395	- Buoy 4					Red nun.	Maintained year round.
							* 40/02
31405	- Buoy 6					Red nun.	Maintained year round.
							* 40/02
31410	- Buoy 7					Green can.	Maintained year round.
							* 40/02
<b>Erie Basin</b>							
36895	- ENTRANCE LIGHT 2	40 40 18 N 74 01 09 W	FI R 2.5s			TR on spindle.	
		*					40/02
37325	<i>Bergen Point Lighted Buoy 14</i>	40 38 34 N 74 08 41 W	FI R 4s		4	Red.	
		*					40/02
<b>NEW YORK HARBOR (Chart 12327)</b>							
<b>Newark Bay</b>							
37385	- Channel Lighted Buoy 2	40 38 40 N 74 08 52 W	Q R		4	Red.	
		*					40/02
37505	- CHANNEL LIGHT 19	40 41 11 N 74 07 48 W	FI G 4s	20	4	SG on skeleton.	
		*					40/02
37530	- LIGHT NB	40 42 28 N 74 07 08 W	FI (2+1) R 6s	30	4	JR on skeleton tower on white base.	
		*					40/02

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

**SECTION II**

**CORRECTIONS TO C. G. LIGHT LIST, VOLUME I LIGHT LIST, 2002**

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
<b>La Motte Passage</b>							
39220	PELOTS POINT N RAILROAD LIGHT	44 50 27 N 73 17 59 W	<b>FI G</b> 4s	20		On pile.	Private aid.
	*	*	*				* 40/02
39225	PELOTS POINT S RAILROAD LIGHT	44 50 24 N 73 18 00 W	<b>FR</b>	20		On pile.	Private aid.
	*						40/02
<b>The Gut North Entrance</b>							
39255	Middle Reef Northeast End Buoy 2 At northeast side of reef.	44 45 54 N 73 19 44 W				Red nun.	
		*					40/02
39290	BOW ARROW POINT N RAILROAD LIGHT	44 45 06 N 73 19 00 W	<b>FG</b>	20		On pile.	Private aid.
			*				40/02
39295	TROMP POINT S RAILROAD LIGHT	44 45 04 N 73 18 59 W	<b>FR</b>	20		On pile.	Private aid.
	*	*					40/02
39320	BURTON ISLAND LIGHT	44 46 39 N 73 11 51 W	<b>FI W</b> 2.5s	14			Maintained from May 15 to Sept. 15. Private aid.
		*					40/02
39361	<i>Bay Saint Armand Lighted Buoy 1</i>	44 44 52 N 73 24 41 W	<b>FI G</b> 4s			Green.	Maintained from May 1 to Oct. 1. Private aid.
		*					40/02
39405	GORDON LANDING FERRY DOCK WEST LIGHT	44 41 19 N 73 21 01 W	<b>FR</b>	18		On pile cluster.	Maintained from Apr. 1 to Jan. 15. Private aid.
		*					40/02
<b>Lake Champlain Underwater Preserve</b>							
<i>Aids maintained from June 1 to Nov. 1. Aids mark historic shipwreck diving sights.</i>							
39635	- Buoy A	44 28 18 N 73 13 43 W				Yellow sphere.	Private aid.
		*					40/02
39640	- Buoy B	44 28 15 N 73 18 59 W				Yellow sphere.	Private aid.
		*					40/02
39645	- Buoy C	44 27 10 N 73 14 42 W				Yellow sphere.	Private aid.
		*					40/02

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

## SECTION II

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME I LIGHT LIST, 2002

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
39650	- Buoy D	44 27 12 N 73 14 26 W				Yellow sphere.	Private aid.  40/02
		*					
39655	- Buoy E	44 33 10 N 73 19 48 W				Yellow sphere.	Private aid.  40/02
		*					
39710	JUNIPER ISLAND LIGHT	44 26 58 N 73 16 35 W	FI W 4s	125	8	On white skeleton tower.	
				*	*		40/02
39810	SPLIT ROCK POINT LIGHT S	44 16 09 N 73 19 17 W	FI W 4s	93	7	NB on red skeleton tower.	
							40/02

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2002

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
2810	DELAWARE CITY LIGHT 1	39 34 46 N 75 35 07 W	FI G 4s	15	4	SG on multi-pile structure.	Light equipment removed when endangered by ice.  40/02
					*		
4125	ROEBLING RANGE FRONT LIGHT	40 07 18 N 74 46 42 W	Oc R 4s	35		On skeleton tower.	Visible on range line only. Lighted throughout 24 hours.  40/02
		*				*	*
4130	ROEBLING RANGE REAR LIGHT 41 yards, 079.8° from front light.		F R	41		On tower with small house on concrete base.	Visible on range line only. Lighted throughout 24 hours.  40/02
			*	*		*	*
<b>Chincoteague Bay</b>							
<b>Greenbackville</b>							
5460	- EAST JETTY LIGHT 2		FI R 2.5s	15	3	TR on pile.	
				*			40/02
6785	- LIGHT 13	37 32 52 N 75 43 51 W	FI G 2.5s	15	3	SG on pile.	
	*	*		*			*
							40/02
6820	- LIGHT 5		FI G 4s	15	4	SG on pile.	Light equipment removed from Dec. 1 to Mar. 15.  40/02
				*			*
6910	- LIGHT 4		Q R	15	4	TR on multi-pile structure.	
						*	40/02

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

**SECTION II**

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2002							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
6945	- Daybeacon 15	37 30 17 N 75 48 12 W				SG on pile.	
		*					40/02
7020	- LIGHT 8		<b>FI R 4s</b>	15	3	TR on multi-pile structure.	
				*		*	40/02
7025	- LIGHT 10		<b>FI R 4s</b>	15	3	TR on pile.	
				*			40/02
7400	- Lighted Bell Buoy 56 75 feet outside channel limit.		<b>FI R 6s</b>		4	Red.	Replaced by nun when endangered by ice.
					*		40/02
9185	- LIGHT 29		<b>FI G 2.5s</b>	25	5	SG on multi-pile structure.	
					*		40/02
<b>HAMPTON ROADS (Chart 12245)</b>							
<b>Hampton Bar</b>							
9380	<b>Old Point Comfort Light</b>	37 00 06 N 76 18 23 W	<b>FI (2) R 12s</b> <b>(W sector)</b> 2s fl 2s ec. 2s fl 6s ec.	54	W 16 R 14	White tower.	White from 265° to 038°.
							* 40/02
9500	- Articulated Light 8	36 57 06 N 76 20 24 W	<b>FI R 2.5s</b>		4	TR on articulated pile.	
						*	40/02
10130	- LIGHT 1		<b>Q G</b>	15	5	SG on pile.	
			*		*		40/02
10135	- LIGHT 2		<b>FI R 2.5s</b>	15	5	TR on pile.	
			*		*		40/02
<b>Hampton River</b>							
10895	- CHANNEL LIGHT 2	36 59 57 N 76 19 08 W	<b>FI R 4s</b>	15	3	TR on multi-pile structure.	
						*	40/02
11940	- CHANNEL LIGHT 40 200 feet outside channel limit.	37 12 48 N 76 38 36 W	<b>FI R 4s</b>	18	4	TR on multi-pile structure.	Ra ref.
						*	40/02
12655	- LIGHT 137 170 feet outside channel limit.		<b>FI G 4s</b>	18	4	SG on multi-pile structure.	
						*	40/02

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

## SECTION II

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2002

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
12780	- LIGHT 163		<b>FI G</b> 4s	18	4	SG on multi-pile structure.	
						*	40/02
14745	- LIGHT 8		<b>FI R</b> 2.5s	15	4	TR on pile.	Light equipment removed from Dec. 15 to Mar. 15.
				*			* 40/02
16645	- LIGHT 3	38 06 01 N 76 24 15 W	<b>FI G</b> 2.5s	17	3	SG on pile.	Light equipment removed from Dec. 1 to Mar. 15.
		*					40/02
16650	- LIGHT 4	38 06 08 N 76 24 27 W	<b>FI R</b> 4s	17	3	TR on pile.	
		*		*			40/02
16675	- LIGHT 2		<b>FI R</b> 4s	18	3	TR on multi-pile structure.	
						*	40/02
<b>Yeocomico River</b>							
16805	- ENTRANCE LIGHT 2		<b>FI R</b> 4s	16	4	TR on pile.	Remains of caisson structure at base of pile.
						*	* 40/02
16810	- LIGHT 3		<b>FI G</b> 6s	16	4	SG on pile.	
				*			40/02
17110	- LIGHT 11 50 feet outside channel limit.		<b>FI G</b> 4s	16	4	SG on pile.	
				*	*		40/02
<b>Mattox Creek</b>							
17475	- LIGHT 1	38 13 18 N 76 57 24 W	<b>FI G</b> 4s	15	4	SG on pile.	
				*			40/02
17490	- LIGHT 4		<b>FI R</b> 4s	15	3	TR on multi-pile structure.	Light equipment removed from Dec. 1 to Mar. 15.
						*	40/02
<b>Monroe Creek</b>							
17515	- ENTRANCE LIGHT 2	38 13 55 N 76 56 58 W	<b>FI R</b> 4s	15	4	TR on pile.	
		*					40/02
17520	- ENTRANCE LIGHT 4		<b>Q R</b>	15	3	TR on pile.	
				*			40/02

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

**SECTION II**

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2002							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
17540	- LIGHT 8		FI R 4s	15	3	TR on pile.	Light equipment removed from Dec. 1 to Mar. 15.
				*			40/02
<b>CHESAPEAKE BAY TO PINEY POINT (Chart 12233)</b>							
<b>St. Jerome Creek</b>							
18795	- LIGHT 1	38 06 55 N 76 20 09 W	FI G 2.5s	15	4	SG on pile.	
		*					40/02
<b>Herring Bay</b>							
19320	- ENTRANCE LIGHT 1	38 44 25 N 76 30 51 W	FI G 2.5s	18	5	SG on pile.	
		*					40/02
19335	ROSE HAVEN CHANNEL LIGHT 1 30 feet outside channel limit.	38 44 02 N 76 32 19 W	Q G	15	3	SG on dolphin.	
		*					40/02
21860	- LIGHT 4		FI R 4s	15	3	TR on pile.	Light equipment removed from Dec. 1 to Mar. 15.
				*			40/02
21905	- LIGHT 13	37 40 10 N 75 49 57 W	FI G 4s	15	4	SG on multi-pile.	Light equipment removed from Dec. 1 to Mar. 15.
					*		40/02
<b>POCOMOKE AND TANGIER SOUNDS (Chart 12228)</b>							
<b>Onancock Creek</b>							
21925	- CHANNEL LIGHT 1		FI G 4s	15	4	SG on multi-pile.	Higher intensity beam toward Pocomoke Sound and Chesapeake Bay.
				*	*		40/02
21990	- LIGHT 6	37 43 18 N 75 48 28 W	FI R 4s	15	3	TR on pile.	Light equipment removed from Dec. 1 to Mar. 15.
				*			40/02
<b>Pocomoke Sound</b>							
22100	- LIGHT 2		FI R 4s	15	3	TR on pile.	
				*	*		40/02
22105	- SHOAL LIGHT 3		FI G 2.5s	15	4	SG on multi-pile structure.	
				*		*	40/02
22110	- LIGHT 5		FI G 4s	15	4	SG on multi-pile structure.	
				*		*	40/02

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

## SECTION II

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2002

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
22130	- LIGHT 2	37 45 18 N 75 48 52 W	FI R 4s	15	3	TR on pile structure.	Light equipment removed from Dec. 1 to Mar. 15.
						*	40/02
	<b>Pocomoke Sound</b>						
22185	- LIGHT 6	37 47 49 N 75 50 19 W	FI R 4s	18	4	TR on multi-pile structure.	
						*	40/02
22205	- LIGHT 6		FI R 2.5s	15	3	TR on pile.	Light equipment removed from Dec. 1 to Mar. 15.
						*	40/02
	<b>Pocomoke Sound</b>						
22250	- LIGHT 7		FI G 2.5s	15	4	SG on multi-pile structure.	
				*		*	40/02
	<b>Hunting Creek</b>						
22260	- LIGHT 2 On edge of shoal.		FI R 4s	15	3	TR on pile.	Light equipment removed from Dec. 1 to Mar. 15.
				*			40/02
22315	- LIGHT 6		FI R 4s	15	3	TR on multi-pile structure.	Light equipment removed from Dec. 1 to Mar. 15.
						*	*
							40/02
	<b>Pocomoke Sound</b>						
22365	- SHOAL LIGHT 8	37 52 28 N 75 49 24 W	FI R 4s	15	4	TR on multi-pile structure.	
				*		*	40/02
22370	- SHOAL LIGHT 9		FI G 2.5s	15	4	SG on multi-pile structure.	
				*		*	40/02
22375	- LIGHT 10		FI R 2.5s	15	4	TR on multi-pile structure.	
				*		*	40/02
	<b>Starling Creek</b>						
22455	- LIGHT 1	37 55 29 N 75 44 11 W	FI G 4s	15	4	SG on multi-pile structure.	HORN: 1 blast ev 30s (3s bl). Maintained from Sept. 15 to June 1.
						*	40/02
22460	- Daybeacon 2					TR on pile.	
	*						40/02
22500	- LIGHT 12		FI R 4s	15	3	TR on multi-pile structure.	
				*	*	*	40/02

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

## SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2002							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
22595	- Channel Daybeacon 22					TR on pile.	
	*						40/02
22615	Shad Landing Park Junction Daybeacon SL	38 08 34 N 75 26 29 W				JR on pile.	
		*					40/02
<b>Tangier Island West Channel</b>							
22725	- LIGHT 1		<b>FI G 2.5s</b>	15	3	SG on pile.	
						*	40/02
22730	- LIGHT 3	37 50 00 N 75 59 54 W	<b>FI G 4s</b>	15	4	SG on pile.	Light equipment removed from Dec. 1 to Mar. 15.
		*					40/02
22910	Hop Point Daybeacon 1	37 59 12 N 75 51 35 W				SG on pile.	
		*					40/02
22915	- CHANNEL LIGHT 13		<b>FI G 4s</b>	15	4	SG on pile.	
				*			40/02
22925	BRICK KILN CHANNEL LIGHT 3		<b>FI G 4s</b>	15	4	SG on pile.	Light equipment removed from Dec. 1 to Mar. 15.
				*	*		40/02
23630	- Channel Lighted Bell Buoy 7		<b>FI G 2.5s</b>		4	Green.	Replaced by LIB of lower intensity from Dec. 1 to Mar. 15.
						*	40/02
23980	- LIGHT 6		<b>Q R</b>	23	3	TR on pile.	Light equipment removed from Dec. 1 to Mar. 15.
							* 40/02
<b>Tar Bay</b>							
24580	- CHANNEL LIGHT 1	38 21 07 N 76 16 20 W	<b>FI G 4s</b>	15	5	SG on pile.	
						*	40/02
24690	- LIGHT 10	38 29 07 N 76 17 08 W	<b>FI R 4s</b>	15	3	TR on pile.	
		*					40/02
24755	- LIGHT 13	38 33 00 N 76 13 16 W	<b>FI G 2.5s</b>	15	4	SG on multi-pile structure.	Light equipment removed from Dec. 1 to Mar. 15.
							* 40/02

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

## SECTION II

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2002

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
25130	- CHANNEL LIGHT 32		FI R 2.5s	15	3	TR on pile.	Light equipment removed from Dec. 1 to Mar. 15.
				*			* 40/02
25140	- CHANNEL LIGHT 34		FI R 4s	15	3	TR on pile.	Light equipment removed from Dec. 1 to Mar. 15.
					*		40/02
25170	- CHANNEL LIGHT 38		FI R 2.5s	15	3	TR on pile.	Light equipment removed from Dec. 1 to Mar. 15.
					*		40/02
28310	- LIGHT 3	35 47 22 N 75 34 00 W	FI G 4s	15	4	SG on pile.	
		*					40/02
29245	- LIGHT 26		FI R 4s	15	3	TR on pile.	
				*			40/02
29270	- LIGHT 35		FI G 2.5s	15	3	SG on pile.	
				*	*		40/02
29385	- CHANNEL LIGHT 16		Q R	15	4	TR on multi-pile structure.	Ra ref.
						*	40/02
31905	- LIGHT 3CS		FI G 4s	15	4	SG on multi-pile structure.	
						*	40/02
<b>Croatan Sound</b>							
31950	- LIGHT 10		FI R 4s	15	3	TR on multi-pile.	Light equipment removed when endangered by ice.
					*		40/02
31955	- Warning Daybeacon					NW on pile worded DANGER SUBMERGED ROCKS.	
		*					40/02
<b>CURRITUCK BEACH LIGHT TO WIMBLE SHOALS (Chart 12204)</b>							
<b>Chicamacomico Channel</b>							
32045	- LIGHT 1CC	35 35 54 N 75 31 09 W	FI G 4s	18	4	SG on multi-pile structure.	Light equipment removed when endangered by ice.
						*	40/02
32545	- WARNING LIGHT J	35 14 18 N 76 24 14 W	FI W 4s	15	5	NW on pile worded DANGER BOMBING RANGE.	
		*					40/02

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

## SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2002							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
<b>Rose Bay</b>							
32735	DEEP COVE LIGHT 1	35 19 49 N 76 23 37 W	<b>FI G</b> 2.5s	15	3	SG on pile.	
						*	40/02
32740	DEEP COVE LIGHT 2		<b>FI R</b> 6s	15	4	TR on pile.	
				*			40/02
33235	LONG POINT FERRY TERMINAL CHANNEL LIGHT 1	35 23 06 N 76 44 39 W	<b>FI G</b> 2.5s	15	3	SG on multi-pile structure.	
		*					40/02
34360	- CHANNEL LIGHT 7	34 58 59 N 76 12 38 W	<b>Q G</b>	15	3	SG on slatted pile structure.	
		*		*	*		40/02
35502	- Buoy 126 A						<i>Remove from list.</i>
							* 40/02
36065	- LIGHT 280	39 15 32 N 74 37 29 W	<b>Q R</b>	15	3	TR-TY on pile.	
				*	*		40/02
36285	- Daybeacon 344	39 10 46 N 74 41 59 W				TR-TY on pile.	
		*					40/02
36580	- LIGHT 437	39 01 58 N 74 48 21 W	<b>FI G</b> 2.5s	15	3	SG-SY on pile.	
						*	40/02
36595	- LIGHT 442		<b>FI R</b> 4s	15	3	TR-TY on pile.	
						*	40/02
36740	- LIGHT 5		<b>FI G</b> 4s	15	4	SG-SY on pile.	
						*	40/02
36765	- LIGHT 12	38 56 58 N 74 53 52 W	<b>FI R</b> 4s	15	4	TR-TY on pile.	
						*	40/02
36780	CAPE MAY CANAL EAST END ENTRANCE LIGHT 14	38 57 08 N 74 54 09 W	<b>FI R</b> 4s	12	3	TR on multi-pile structure.	
						*	40/02
37770	- LIGHT 159		<b>FI G</b> 4s	15	4	SG-SY on multi-pile structure.	
				*		*	40/02

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

## SECTION II

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2002

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
37860	- LIGHT 12	35 54 54 N 76 00 13 W	<b>F I R</b> 4s	15	3	TR-TY on pile.	
				*			40/02
37895	- LIGHT 26		<b>F I R</b> 2.5s	15	3	TR-TY on pile.	Light equipment removed Dec. 1 to Mar. 15.
				*			* 40/02
<b>Core Creek</b>							
<i>Aids located 30 - 35 feet outside channel limit.</i>							
38385	- LIGHT 19	34 48 25 N 76 41 08 W	<b>Q G</b>	15	3	SG-SY on pile.	
			*				40/02
38495	- LIGHT 34		<b>Q R</b>	15	4	TR-TY on pile.	
				*			40/02
39651	- Buoy 135A						<i>Remove from list.</i>
							* 40/02
40045	- Buoy 2	33 54 55 N 78 01 10 W				Red nun with yellow triangle.	
						*	40/02
40325	- LIGHT 77		<b>F I G</b> 4s	15	3	SG-SY on multi-pile structure.	
						*	40/02

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2002

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*1025.5	Middle Sambo Shoal Daybeacon	24 29 18 N 81 40 36 W				NW on pile worded DANGER SHOAL.	40/02
*1030.2	Western Sambo North Shoal Daybeacon	24 29 12 N 81 42 30 W				NW on pile worded DANGER SHOAL.	40/02
*1030.4	Western Sambo West Shoal Daybeacon	24 28 48 N 81 43 10 W				NW on pile worded DANGER SHOAL.	40/02
1345 21585	NEW PASS ENTRANCE LIGHT NP	27 18 54 N 82 35 53 W	<b>Mo (A) W</b>	16	5	MR on pile.	
	*		*		*	*	40/02
2115	RABBIT ISLAND CHANNEL RANGE FRONT LIGHT	30 20 24 N 79 51 48 W	<b>Q R</b>	25		KRW-I on tower on pile.	Visible 1.5° each side of range line.
		*					* 40/02

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

**SECTION II**

**CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2002**

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
2120	RABBIT ISLAND CHANNEL RANGE REAR LIGHT 1,130 yards, 009.1° front light.		<b>Iso R</b> 6s	42		KRW on tower on pile.	Visible 1.5° each side of range line.  * 40/02
2385	FORT SUMTER RANGE FRONT LIGHT	32 44 48 N 79 51 48 W	<b>FI W</b> 2.5s	26		On skeleton tower.	Visible 0.5° each side of range line. Lighted throughout 24 hours.  * 40/02
2390	FORT SUMTER RANGE REAR LIGHT 1,902 yards, 299.3° from front light.		<b>Iso W</b> 6s	92		On skeleton tower on piles.	Visible 0.5° each side of range line. Lighted throughout 24 hours.  * 40/02
<b>Charleston Harbor North Channel</b>							
2485	- RANGE A FRONT LIGHT	32 46 54 N 79 54 12 W	<b>Q W</b>	25		On skeleton tower on piles.	Visible 1.5° each side of range line. Lighted throughout 24 hours.  * 40/02
7115	ST. JOHNS BAR CUT RANGE FRONT LIGHT	30 24 14 N 79 51 48 W	<b>Q W</b>	19		KRW on tower on piles.	Visible 0.5° each side of range line.  * 40/02
7120	ST. JOHNS BAR CUT RANGE REAR LIGHT 2,328 yards, 276.7° from front light.		<b>Iso W</b> 6s	80		KRW on skeleton tower on piles.	Visible 0.5° each side of range line.  * 40/02
7287	- UPPER RANGE FRONT LIGHT	30 22 42 N 81 27 12 W	<b>Q G</b>	20		KRW on skeleton tower on piles.	Visible 1.5° each side of range line.  * 40/02
7290	- UPPER RANGE REAR LIGHT 432 yards, 128.6° from front light.		<b>Iso G</b> 6s	37		KRW on skeleton tower on piles.	Visible 1.5° each side of range line.  * 40/02
<b>St. Johns River</b>							
7295	TRAINING WALL RANGE FRONT LIGHT	30 23 48 N 81 28 36 W	<b>Q W</b>	21		KRW on skeleton tower on piles.	Visible 1.5° each side of range line.  * 40/02
7300	TRAINING WALL RANGE REAR LIGHT 602 yards, 309.1° from range front light.		<b>Iso W</b> 6s	42		KRW on skeleton tower on piles.	Visible 1.5° each side of range line.  * 40/02

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

## SECTION II

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2002

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
7350	- RANGE FRONT LIGHT	30 23 36 N 81 30 12 W	<b>Q W</b>	22		KRW on dolphin.	Visible 0.5° each side of range line.  * 40/02
7355	- RANGE REAR LIGHT 996 yards, 078.9° from front light.		<b>Iso W 6s</b>	106		KRW on tower on concrete base.	Visible 0.5° each side of range line.  * 40/02
7375	DAMES POINT CUTOFF RANGE FRONT LIGHT	30 22 54 N 81 33 42 W	<b>Q W</b>	18		KRW on skeleton tower on pile structure.	Visible 0.5° each side of range line.  * 40/02
7380	DAMES POINT CUTOFF RANGE REAR LIGHT 952 yards, 258.9° from front light.		<b>Iso W 6s</b>	49		KRW on skeleton tower on pile structure.	Visible 0.5° each side of range line.  * 40/02
9555	- LIGHT 10  *		<b>FI R 2.5s</b>	14	3	TR on pile.  *	  40/02
<b>CAPE CANAVERAL TO BETHEL SHOAL (Chart 11476)</b>							
<b>Canaveral Harbor</b>							
9575	- APPROACH CHANNEL RANGE FRONT LIGHT	28 25 00 N 80 35 06 W	<b>Q W</b>	25		KRG on skeleton tower.	Visible 1.5° each side of range line.  * 40/02
9580	- APPROACH CHANNEL RANGE REAR LIGHT 2,000 yards, 310° from front light.		<b>Iso W 6s</b>	82		KRG on skeleton tower.	Visible 1.5° each side of range line.  * 40/02
9630	- ENTRANCE CHANNEL RANGE FRONT LIGHT	28 24 36 N 80 37 54 W	<b>Q G</b>	25		KRW on skeleton tower on piles.	Visible 1.5° each side of range line.  * 40/02
9635	- ENTRANCE CHANNEL RANGE REAR LIGHT 667 yards, 270° from front light.		<b>Iso G 6s</b>	54		KRW on skeleton tower on piles.	Visible 1.5° each side of range line.  * 40/02
9820	- ENTRANCE RANGE FRONT LIGHT	27 28 10 N 80 18 12 W	<b>Q G</b>	15		KRW on skeleton tower on piles.	Visible 4° each side of rangeline.  * 40/02
9825	- ENTRANCE RANGE REAR LIGHT 1,296 yards, 259.6° from front light.		<b>Iso G 6s</b>	50		KRW on skeleton tower on piles.	Visible 4° each side of range line.  * 40/02

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

**SECTION II**

**CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2002**

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
	<b>*Delete Heading: *Fort Pierce Inlet</b>						
9940	- INNER HARBOR RANGE FRONT LIGHT						<i>Remove from list.</i>  * 40/02
	<b>*Add Heading: *Fort Pierce Inlet</b>						
9945	- INNER HARBOR RANGE REAR LIGHT 265 yards, 061.7° from front light.		<b>Iso G 6s</b>	32		KRW on skeleton tower on piles.	Visible all around; higher intensity on rangeline.  40/02
10185	LAKE WORTH ENTRANCE RANGE FRONT LIGHT	26 46 18 N 80 02 30 W	<b>Q W</b>	30		KRW on skeleton tower on dolphin.	Visible 14° each side of range line.  * 40/02
10190	LAKE WORTH ENTRANCE RANGE REAR LIGHT 440 yard, 271.5° from front light.		<b>Iso W 6s</b>	55		KRW on skeleton tower.	Visible 14° each side of range line.  * 40/02
10505	GOVERNMENT CUT RANGE FRONT LIGHT	25 45 12 N 80 06 30 W	<b>Q W</b> FI W 4s	25 28	5	KRW on tower on piles.	Visible 1.5° each side of range line. Passing light visible around horizon.  * 40/02
10510	GOVERNMENT CUT RANGE REAR LIGHT 785 yards, 114.8° from front light.		<b>Iso W 6s</b> FI W 4s	50 25	5	KRW on tower on piles.	Visible 1.5° each side of range line. Passing light visible around horizon.  * 40/02
14815	- RANGE FRONT LIGHT	24 32 12 N 81 48 24 W	<b>Q G</b> FI R 4s	32 32		KRW on skeleton tower on piles.	Visible 1.5° each side of range line. Passing light obscured from 326° to 026°.  * 40/02
14820	- RANGE REAR LIGHT 1,408 yards, 356° from front light.		<b>Iso G 6s</b>	75		KRW on skeleton tower on piles.	Visible 1.5° each side of range line.  * 40/02
21190	- Daybeacon 24  *					TR on pile.  *	  40/02
21465	- Daybeacon 2  *	27 15 58 N 82 33 52 W  *				TR on pile.  *	  40/02
21473	- Daybeacon 2A  *	27 16 21 N 82 34 14 W  *				TR on pile.  *	  40/02

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

## SECTION II

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2002

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*21477	- Buoy 3C					Green can.	40/02
<b>New Pass</b>							
21585 1345	- NEW PASS ENTRANCE LIGHT NP	27 18 54 N 82 35 53 W	<b>Mo (A) W</b>	16	5	MR on pile.	
	*		*		*	*	40/02
21585.5	- Channel Buoy 2A					Red nun.	40/02
	*						40/02
22080	- LIGHT 24A		<b>F I R 2.5s</b>		14	TR on pile.	
	*		*		*		40/02
22100	- LIGHT 29		<b>Q G</b>	14	3	SG on pile.	
	*		*	*	*		40/02
22480 60490	- RANGE FRONT LIGHT	27 41 18 N 82 34 42 W	<b>Q W</b>	23		KRW-I on piles.	Visible 0.5° each side of range line.  * 40/02
22485 60495	- RANGE REAR LIGHT 1,700 yards, 037.7° from front light.		<b>Iso W 6s</b>	57		KRW on piles.	Visible 0.5° each side of range line.  * 40/02
<b>Port Manatee Channel</b>							
22505	- RANGE FRONT LIGHT	27 37 48 N 82 33 30 W	<b>Q G (Night) F W (Day)</b>	142		KRW on tower.	Visible 4° each side of range line.  * 40/02
22600	- RANGE FRONT LIGHT	27 41 55 N 82 32 50 W	<b>Q W</b>	17		On piles.	Visible 1.5° each side of range line. Lighted throughout 24 hours.  * 40/02
22605	- RANGE REAR LIGHT 1,790 yards, 061.2° from front light.		<b>Iso W 6s</b>	50		On skeleton tower on piles.	Visible 1.5° each side of range line. Lighted throughout 24 hours.  * 40/02
22760	- RANGE FRONT LIGHT	27 45 48 N 82 31 14 W	<b>Q W</b>	15		On small house on piles.	Visible 1.5° each side of range line. Lighted throughout 24 hours.  * 40/02
22765	- RANGE REAR LIGHT 1,271 yards, 017.9° from front light.		<b>Iso W 6s</b>	50		On skeleton tower on piles.	Visible 1.5° each side of range line. Lighted throughout 24 hours.  * 40/02

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

**SECTION II**

**CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2002**

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
22810	- NORTH RANGE FRONT LIGHT	27 47 28 N 82 31 24 W	<b>FI G</b> 2.5s	17		KRW on piles.	Visible 0.5° each side of range line. Lighted throughout 24 hours.  * 40/02
22815	- NORTH RANGE REAR LIGHT 1,551 yards, 359.6° from front light.		<b>Iso G</b> 6s	51		KRW on skeleton tower on piles.	Visible 0.5° each side of range line. Lighted throughout 24 hours.  * 40/02
23435	- NORTH RANGE FRONT LIGHT	27 54 24 N 82 26 18 W	<b>Iso W</b> 2s (Day) <b>Iso W</b> 2s (Night)	23 25		On skeleton tower on piles.	Visible 2° each side of rangeline.  * 40/02
23440	- NORTH RANGE REAR LIGHT 2,174 yards, 005.3° from front light.		<b>Iso W</b> 6s (Day) <b>Iso W</b> 6s (Night)	98 100		On skeleton tower on piles.	Visible 2° each side of rangeline.  * 40/02
30745	- RANGE FRONT LIGHT	18 27 25 N 66 07 42 W	<b>Q G</b>	23		KRW on skeleton tower on piles.	Visible 0.5° each side of rangeline. Lighted throughout 24 hours.  * 40/02
30750	- RANGE REAR LIGHT 240 yards, 180.5° from front light.	18 27 18 N 66 07 43 W	<b>Iso G</b> 6s	56		KRW on skeleton tower.	Visible 0.5° each side of rangeline. Lighted throughout 24 hours.  * 40/02
<b>Dawho River</b>							
34950	- Buoy 111	32 37 25 N 80 17 01 W				Green can with yellow square.	  * 40/02
<b>Sapelo Sound</b>							
36630	- Daybeacon 136A			12		TR on pile.	  * 40/02
41200	- LIGHT 26	28 38 01 N 80 48 27 W	<b>FI R</b> 4s	12	3	TR-TY on pile.	  * 40/02
56135	- Daybeacon 72						Remove from list.  * 40/02
60490 22480	- RANGE FRONT LIGHT	27 41 18 N 82 34 42 W	<b>Q W</b>	23		KRW-I on piles.	Visible 0.5° each side of range line.  * 40/02

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

## SECTION II

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV LIGHT LIST, 2002

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*285	<i>BP America-101-1 Lighted Mooring Buoy</i>	28 53 15 N 88 05 09 W	FI W 4s			White with blue band.	Private aid.  40/02
<b>St. Louis Bay</b>							
9040	DUPONT DIFFUSER PLATFORM LIGHTS (2)	30 22 18 N 89 19 06 W	FI W 4s	17		NW on protective structure worded DANGER SUBMERGED PIPE.	Private aids.  40/02
				*			40/02
9120	- LIGHT 5	30 14 18 N 89 25 24 W	FI G 2.5s	17	3	SG on pile.	Ra ref.  40/02
						*	40/02
16525	- RANGE REAR LIGHT 2,997 yards, 012.2° from front light.	29 07 24 N 90 13 01 W	Oc G 4s	80		KRW on platform.	  40/02
				*			40/02
22425	- RANGE T FRONT LIGHT	30 00 30 N 94 58 36 W	F G	40		On skeleton tower on block.	Lighted throughout 24 hours.  40/02
				*			40/02
22430	- RANGE T REAR LIGHT 740 yards, 108° from front light.		F G	71		On skeleton tower on block.	Lighted throughout 24 hours.  40/02
				*			40/02
25965	- RANGE A FRONT LIGHT	28 26 34 N 96 20 42 W	FI W 2.5s (Day) FI W 2.5s (Night)	22 24		On pile with platform.	Visible all around; higher intensity on range line.  40/02
		*	*	*		*	*
25967	- RANGE A FRONT PASSING LIGHT						<i>Remove from list.</i>  40/02
							*
25970	- RANGE A REAR LIGHT 1,239 yards, 316.7° from front light.		Iso W 6s	76		On skeleton tower on piles.	Lighted throughout 24 hours.  40/02
							*

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2002

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
210	<b>Point Arguello Light</b>	34 34 37 N 120 38 55 W	FI W 15s	100	9	On single post. 20	  40/02
							*
<b>YAQUINA HEAD TO COLUMBIA RIVER (CHART 18520)</b>							
655 9780	<i>Depoe Bay Approach Lighted Whistle Buoy DB</i>	44 48 29 N 124 05 19 W	Mo (A) W		6	Red and white stripes.	No topmark will be shown on this aid due to weather.  40/02
							*

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

**SECTION II**

**CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2002**

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
<b>APPROACHES TO STRAIT OF JUAN DE FUCA (Chart 18480)</b>							
740 16075	<i>Quillayute River Approach Lighted Whistle Buoy Q</i>	47 53 08 N 124 40 34 W	<b>Mo (A) W</b>		5	Red and white stripes.	No topmark will be shown on this aid due to weather.  * 40/02
755 16135	<i>Strait of Juan de Fuca Traffic Lane Separation Lighted Buoy J</i>	48 29 14 N 124 43 39 W	<b>FI Y 4s</b>		4	Yellow.	RACON: O (---).  * 40/02
1568	- SUBMERGED JETTY LIGHT M	32 41 11 N 117 13 37 W	<b>FI Y 4s</b>	15	4	NW on pile worded: DANGER SUBMERGED JETTY.	 * 40/02
2315	-Buoy 5					Green Can.	 * 40/02
*Delete Headings: *SAN NICOLAS ISLAND (Chart 18755) *San Nicolas Island							
2580	- SOUTH SIDE LIGHT						Remove from list.  * 40/02
*Add Headings: *SAN NICOLAS ISLAND (Chart 18755) *San Nicolas Island							
2585	- East End Lighted Bell Buoy 3	33 13 24 N 119 23 54 W	<b>FI G 4s</b>		4	Green.	 40/02
2595	- North Side Light						Remove from list.  * 40/02
<b>SANTA CATALINA ISLAND (Chart 18757)</b>							
2605	<b>Santa Catalina Island East End Light</b>	33 18 06 N 118 19 00 W	<b>FI W 6s</b>	212	10	On post.	Visible from 253° to 068°, partially obscured by hills elsewhere.  * 40/02
3640	- SOUTH JETTY LIGHT 2	34 09 22 N 119 16 10 W	<b>FI R 2.5s</b>	35	6	On rectangular structure.	The fog signal can be activated upon request to the Coast Guard via VHF-FM Ch 16. HORN: 1 blast ev 15s (1s bl).  * 40/02
3700	- SOUTH JETTY LIGHT 6	34 24 17 N 119 16 10 W	<b>FI R 4s</b>	26	6	TR on pole.	The fog signal can be activated upon request to the Coast Guard via VHF-FM Ch 16. HORN: 1 blast ev 10s (1s bl).  * 40/02

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

## SECTION II

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2002

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
3775	- Lighted Buoy 7		<b>Q G</b>		3	Green.	
					*		40/02
<b>Morro Bay Channel</b>							
<i>Buoys inside the harbor are set to best mark the channel and are not charted.</i>							
3840	Morro Bay Approach Lighted Whistle Buoy MB	35 21 36 N 120 52 50 W	<b>Mo (A) W</b>		5	Red and white stripes.	
							40/02
4820	San Francisco Bay Preferred Channel Lighted Buoy SC	37 46 32 N 122 21 57 W	<b>FI G (2+1)</b>			Green.	
	*	*	*		*		40/02
<b>*Delete Heading: *Oakland Airport</b>							
4827	- Security Zone Buoy A						Remove from list.
							* 40/02
4827.1	- Security Zone Buoy B						Remove from list.
							* 40/02
4827.2	- Security Zone Buoy C						Remove from list.
							* 40/02
4827.3	- Security Zone Buoy D						Remove from list.
							* 40/02
<b>*Delete Heading: *San Francisco Airport</b>							
4971	- Security Zone Buoy A						Remove from list.
							* 40/02
4972	Security Zone Buoy B						Remove from list.
							* 40/02
4973	- Security Zone Buoy C						Remove from list.
							* 40/02
4974	- Security Zone Buoy D						Remove from list.
							* 40/02
8917	Sause Brothers Lighted Mooring Buoy SB	43 24 12 N 124 16 30 W	<b>FI Y 4s</b>			White with blue bands.	Private aid.
	*		*				40/02
*9707	- Lighted Buoy WR23	44 35 04 N 124 01 20 W	<b>Q G</b>		3	Green.	
							40/02

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

**SECTION II**

**CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2002**

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
<b>Depoe Bay</b>							
9780 655	- Approach Lighted Whistle Buoy DB	44 48 29 N 124 05 19 W	<b>Mo (A) W</b>		6	Red and white stripes.	No topmark will be shown on this aid due to weather.  * 40/02
10633	COLUMBIA RIVER GEODETIC SURVEY LIGHT	46 11 06 N 123 11 12 W	<b>FI Y 10s</b>	10		On dolphin.	Private aid.  * 40/02
*10717	WILLOW GROVE BOAT LAUNCH LIGHT 1	46 10 23 N 123 05 05 W	<b>FI G 4s</b>	10		On breakwall.	Private aid.  40/02
*10718	WILLOW GROVE BOAT LAUNCH LIGHT 2	46 10 24 N 123 05 03 W	<b>FI R 4s</b>	10			Private aid.  40/02
<b>Lewis and Clark Bridge</b>							
10811	- Approach Buoy 1	46 06 25 N 122 57 40 W				Green can.	Private aid.  * 40/02
10812	- Approach Buoy 2	46 06 15 N 122 57 46 W				Red nun.	Private aid.  * 40/02
10813	- Approach Buoy 3	46 06 22 N 122 57 35 W				Green can.	Private aid.  * 40/02
10814	- Approach Buoy 4	46 06 12 N 122 57 41 W				Red nun.	Private aid.  * 40/02
11235	MATHEWS POINT EAST LIGHT	45 38 44 N 122 43 59 W	<b>FI G</b>	34		On pile.	Private aid.  * 40/02
11240	MATHEWS POINT WEST LIGHT	45 38 45 N 122 44 06 W	<b>FI G</b>	34		On pile.	Private aid.  * 40/02
11600	SAND ISLAND LIGHT 66	45 33 02 N 122 14 10 W	<b>FI R 4s</b>	18	4	TR on dolphin.	Higher intensity beam up and down channel.  * 40/02
*Delete Headings: *FRANKLIN D. ROOSEVELT LAKE (Southern Part) (Chart 18551) *Franklin D. Roosevelt Lake (Above Coulee Dam) *U.S. Bureau of Reclamation Boat Ramp							
14100	- Buoy 2						Remove from list.  * 40/02

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

## SECTION II

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2002

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
14105	- Buoy 4						Remove from list. * 40/02
14110	- Buoy 5						Remove from list. * 40/02
14115	- Buoy 6						Remove from list. * 40/02
14120	- Buoy 7						Remove from list. * 40/02
<p><b>*Change Headings to Read:</b>  <b>*FRANKLIN D. ROOSEVELT LAKE (Southern Part) (Chart 18551)</b>  <b>*Franklin D. Roosevelt Lake</b></p> <p><i>Aids maintained from May 15 to Nov. 1.</i></p>							
14125	- LIGHT A	47 56 48 N 118 56 12 W	<b>FI W 4s</b>	12	6	NB on box.	40/02
<p><b>APPROACHES TO STRAIT OF JUAN DE FUCA (Chart 18480)</b></p> <p><b>Quillayute River</b></p>							
16075 740	- Approach Lighted Whistle Buoy Q	47 53 08 N 124 40 34 W	<b>Mo (A) W</b>		5	Red and white stripes.	No topmark will be shown on this aid due to weather. * 40/02
16090	- DIRECTION LIGHT	47 54 27 N 124 38 41 W	<b>Iso W 6s (R &amp; G Sectors)</b>	25		On pile. On same structure as Quillayute River Entrance Light 3.	White visible 1° each side of centerline of channel bearing 005.5°. Red visible from 003° to 004.5°. Green visible from 006.5° to 008°. * 40/02
16095	- ENTRANCE LIGHT 3	47 54 27 N 124 38 41 W	<b>FI G 4s</b>	25	4	SG on pile. On same structure as Quillayute River Direction Light.	Obscured from 003° to 008°. * 40/02
16105	- BOAT BASIN LIGHT 1	47 54 38 N 124 38 17 W	<b>FI G 4s</b>	13	3	SG on dolphin.	* 40/02
16110	- BOAT BASIN LIGHT 2	47 54 37 N 124 38 17 W	<b>FI R 4s</b>	13	3	TR on dolphin.	* 40/02

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

**SECTION II**

**CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2002**

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
<b>STRAIT OF JUAN DE FUCA ENTRANCE (Chart 18460)</b>							
<b>Strait of Juan De Fuca</b>							
16135 755	- <i>Traffic Lane Separation Lighted Buoy J</i>	48 29 14 N 124 43 39 W	FI Y 4s		5	Yellow.	RACON: O (---).  40/02
		*					
16165	NEAH BAY LIGHT 4	48 22 30 N 124 36 01 W	FI R 2.5s		3	TR on pile structure.	
	*	*	*		*	*	40/02
16205	Ideal Cement Range Rear Daybeacon 133 yards, 180° from front daybeacon.						<i>Remove from list.</i>  * 40/02
16770	SHILSHOLE BAY BOAT BASIN LIGHT 2	47 41 16 N 122 24 18 W	Q R	17	5	TR on jetty.	
	*						40/02
16790 18140	SHILSHOLE BAY BREAKWATER LIGHT 3	47 40 38 N 122 24 43 W	FI G 2.5s	22	7	SG on white house.	
		*			*		40/02
16800	<b>West Point Light</b>	47 39 43 N 122 26 09 W	AI WR 10s 0.2s W fl 4.8s ec. 0.2s R fl 4.8s ec.	27	W 19 R 16	White octagonal tower on building. 23	Lighted throughout 24 hours. Emergency light: Iso W 6s. HORN: 1 blast ev 30s (3s bl).  40/02
		*					
18135	- Channel Buoy 4	47 40 34 N 122 24 48 W				Red nun.	
		*					40/02
18140 16790	- BREAKWATER LIGHT 3	47 40 38 N 122 24 43 W	FI G 2.5s	22	7	SG on white house.	
		*					40/02
18145	- Channel Buoy 6	47 40 25 N 122 24 38 W				Red nun.	
		*					40/02
<b>Union Bay Channel</b>							
18245	- Buoy 15	47 38 51 N 122 17 25 W				Green can.	
		*					40/02
18255	- Buoy 17	47 38 51 N 122 17 25 W				Green can.	
		*					40/02

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

## SECTION II

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2002

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
18260	- Buoy 18	47 38 49 N 122 16 53 W				Red nun.	
		*					40/02
18265	- Buoy 19	47 38 51 N 122 16 51 W				Green can.	
		*					40/02
<b>Lake Washington</b>							
18270	WEBSTER POINT LIGHT 21	47 38 51 N 122 16 34 W	<b>FI G 4s</b>	19	6	SG on white house on pile structure.	Light obscured from 121° to 199°.
		*					40/02
18285	<i>North Lake Washington Monitoring Lighted Buoy</i>	47 40 45 N 122 13 52 W	<b>FI Y 4s</b>			Yellow.	Private aid.
		*					40/02
18320	<i>Central Lake Washington Monitoring Lighted Buoy</i>	47 38 07 N 122 16 14 W	<b>FI Y 4s</b>			Yellow.	Private aid.
	*	*					40/02
18388	<i>South Lake Washington Monitoring Lighted Buoy.</i>	47 35 35 N 122 16 24 W	<b>FI Y 4s</b>			Yellow.	Private aid.
		*					40/02
19495	- Lighted Bell Buoy 16	48 38 27 N 122 42 53 W	<b>Q R</b>		4	Red.	
		*					40/02
19810	<b>Saturna Island Light</b> (C)	48 47 00 N 123 02 42 W	<b>FI W 15s</b> <b>(R sector)</b>	121	W 17 R 8	On red skeleton tower.	White light visible from 149° to 060°; red light visible from 156° to 211.5°. Emergency light.
						*	40/02
19870	<i>Alden Bank Lighted Bell Buoy B</i>	48 47 03 N 122 48 57 W	<b>FI (2+1) R 6s</b>		5	Red and green bands.	
		*					40/02
25827.1	<i>C-LAB-1 Lighted Research Buoy</i>						Remove from list.
							* 40/02
<b>JOHNSTON ATOLL (Chart 83637)</b>							
<b>Johnston Atoll</b>							
30080	- Channel Entrance Lighted Buoy 2	16 42 44 N 169 31 01 W	<b>FI R 2.5s</b>		4	Red.	
		*					40/02

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

**SECTION II**

**CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII LIGHT LIST, 2002**

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
3345	Niagara Falls Safety Buoy A Marks safety zone above Niagara Falls.	43 04 06 N 79 01 07 W				White can with orange bands and danger symbol.	Maintained from May 1 to Oct. 28.  * 40/02
3350	Niagara Falls Safety Buoy B Marks safety zone above Niagara Falls.					White can with orange bands and danger symbol.	Maintained from May 1 to Oct. 28.  * 40/02
3355	Niagara Falls Safety Buoy C Marks safety zone above Niagara Falls.					White can with orange bands and danger symbol.	Maintained from May 1 to Oct. 28.  * 40/02
3356	Niagara Falls Safety Buoy D Marks safety zone above Niagara Falls.					White can with orange bands and danger symbol.	Maintained from May 1 to Oct. 28.  * 40/02
3357	Niagara Falls Safety Buoy E Marks safety zone above Niagara Falls.					White can with orange bands and danger symbol.	Maintained from May 1 to Oct. 28.  * 40/02
3358	Niagara Falls Safety Buoy F Marks safety zone above Niagara Falls.					White can with orange bands and danger symbol.	Maintained from May 1 to Oct. 28.  * 40/02
4100	Forest City Yacht Club Buoy 4					Red nun.	Maintained from May 1 to Oct. 14.  * 40/02
4345	- Lighted Buoy 5		<b>FI G 4s</b>		4	Green.	Maintained from May 1 to Oct. 14.  * 40/02
<b>*Change Note to Read:</b>							
<b>Muddy Creek</b>							
<i>*Buoys maintained from May 1 to Oct. 14. Due to silting, buoys may be relocated without prior notice.</i>							
5060	- Buoy 7					Green can.	40/02
<b>*Change Note to Read:</b>							
<b>Sandusky River</b>							
<i>*Buoys maintained from May 1 to Oct. 14. Due to silting, buoys may be relocated without prior notice.</i>							
5090	- Daybeacon 13					SG on pile.	40/02

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

**SECTION II**

**CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII LIGHT LIST, 2002**

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
9830	STOKES POINT WHARF LIGHT (C)	42 44 05 N 82 28 44 W	<b>Iso R</b> 2s	30 <b>9</b>		White circular tower with red top. 24	
		*					40/02
11510	NOAA Lighted Weather Buoy 45003	45 21 16 N 82 50 22 W	<b>FI (4) Y</b> 20s 1s fl 1.5s ec. 1s fl 1.5s ec. 1s fl 1.5s ec. 1s fl 11.5s ec.			Yellow, disc-shaped hull.	Replaced by nun from Nov. 14 to May 14.
							* 40/02
18750	- Lighted Buoy 3		<b>FI G</b> 2.5s			Green.	Maintained from Apr. 1 to Nov. 21.
							* 40/02
19320	Big Bay Buoy 1					Green can.	Maintained from Apr. 14 to Nov. 14.
							* 40/02
19325	Big Bay Buoy 2					Red nun.	Maintained from Apr. 14 to Nov. 14.
							* 40/02
19330	Big Bay Buoy 3					Green can.	Maintained from Apr. 14 to Nov. 14.
							* 40/02
20735	Texas Rock Buoy 2					Red nun.	Maintained from Apr. 14 to Nov. 14.
							* 40/02
20880	- Buoy 1	44 05 36 N 87 38 54 W				Green can.	Maintained from Apr. 14 to Nov. 14.
							* 40/02
20885	- Buoy 2					Red nun.	Maintained from Apr. 14 to Nov. 14.
							* 40/02
20890	- Buoy 3					Green can.	Maintained from Apr. 14 to Nov. 14.
							* 40/02
<b>Little Bay De Noc</b>							
21730	Saunders Point Buoy 13	45 50 54 N 86 59 42 W				Green can.	Maintained from Apr. 14 to Nov. 14.
							* 40/02
21740	Saunders Point Shoal Inside Buoy 15 Marks north side of shoal.	45 51 06 N 86 59 54 W				Green can.	Maintained from Apr. 14 to Nov. 14.
							* 40/02

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.

## SECTION II

### CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII LIGHT LIST, 2002

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
21745	Kipling Channel Buoy 8	45 51 51 N 86 59 59 W				Red nun.	Maintained from Apr. 14 to Nov. 14.
							* 40/02

**Note:** Asterisks (\*) indicate that column(s) in which a correction has been made or new information added.  
Denotes a new entry when preceding the station number.