

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME I LIGHT LIST, 2002							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
367	<i>University of Maine Research Lighted Buoy A</i>	42 31 05 N 70 33 56 W	FI Y 4s		4	Yellow.	Marked ODAS.
	*						6/03
4025	Compass Island Ledge Isolated Danger Buoy DLL East of ledge.					Black and red with two black spherical topmarks.	
	*						6/03
4915	- LIGHT 21	44 04 11 N 69 10 47 W	FI W 6s	14	5	SG on white skeleton tower.	
						*	6/03
Merriconeag Sound Approach							
6675 40	Halfway Rock Light	43 39 21 N 70 02 12 W	FI R 5s	77	19	White tower attached to dwelling. 76	Emergency light of reduced intensity when main light is extinguished. HORN: 2 blasts ev 30s (2s bl-2s si-2s bl-24s si). Operates continuously.
		*					6/03
8065	Phillip Rock Daybeacon 5					SG on spindle.	
						*	6/03
9975 350	Bakers Island Light	42 32 11 N 70 47 09 W	AI W R 20s	111	W 16 R 14	White conical tower.	Emergency light FI W 10s and horn of reduced intensity when main light or horn is extinguished. HORN: 1 blast ev 30s (3s bl).
		*					6/03
10425	<i>Fifteen-foot Rock Lighted Bell Buoy FR</i>	42 30 12 N 70 49 06 W	FI (2+1) R 6s		4	Red and green bands.	
						*	6/03
	*Add Heading: *Chelsea River						
*10974	Chelsea Creek NSTAR Hazard Buoy					White can with orange bands.	Marked: DANGER CABLE CROSSING.
							6/03
	*Delete Heading: *Chelsea River						
10975	- <i>Channel Lighted Buoy 2</i>	42 23 18 N 71 01 06 W	FI R 2.5s		3	Red.	
							6/03
	Western Way						
11529	- LIGHT 1	42 16 49 N 70 56 20 W	FI G 4s	31	5	SG on pile.	
		*					6/03

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME I LIGHT LIST, 2002

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
13550	- Lighted Buoy 8	41 32 43 N 69 58 56 W	FI R 6s		4	Red.	
		*					6/03
13650 545	Nantucket (Great Point) Light	41 23 24 N 70 02 54 W	FI W 5s (R sector)	71	W 14 R 12	On white tower. 70	Red from 084° to 106°. Covers Cross Rip and Tuckernuck Shoals.
							6/03
	Cleveland Ledge Channel						
16085	Cleveland East Ledge Light	41 37 51 N 70 41 39 W	FI W 10s	74	15	White cylindrical tower and dwelling on red caisson.	Emergency light of reduced intensity when main light is extinguished. RACON: C (-•-•). HORN: 1 blast ev 15s (2s bl).
						*	6/03
16731 16040	DUMPLING ROCKS LIGHT 7 On rock.	41 32 18 N 70 55 17 W	FI G 6s	52	8	SG on skeleton tower.	
		*					6/03
17525	- Channel Buoy 26					Red nun.	
		*					6/03
	Narragansett Bay						
	Eastern Approach						
17675	<i>Narragansett Bay</i> Entrance Lighted Whistle Buoy NB	41 23 00 N 71 23 24 W	Mo (A) W		6	Red and white stripes with red spherical topmark.	RACON: B (-•••). *
							6/03
18255	Fork Rock Buoy	41 40 30 N 71 20 51 W				Red nun with green bands.	
		*					6/03

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2002

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
720 29328	<i>Beaufort Inlet Channel Lighted Whistle Buoy BM</i>		Mo (A) W		6	Red and white striped with red spherical topmark.	RACON: M(- -). *
						*	6/03
8870	- Lighted Buoy 45		FI G 2.5s		4	Green.	Replaced by LIB of lower intensity from the first Tuesday after Thanksgiving to Mar. 15.
						*	6/03
14705	- Daybeacon 2 10 feet outside channel limit.			20		TR on pile.	
				*			6/03

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2002							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
17690	- LIGHT 5		FI G 4s	16	5	SG on pile.	
				*		*	6/03
18600	- Lighted Buoy 90		FI R 4s		4	Red.	Replaced by LIB of lower intensity from Dec. 1 to Mar. 15.
					*		6/03
19725	GREENBURY POINT SHOAL LIGHT	38 58 06 N 76 27 15 W	FI W 4s	40	6	NR on red skeleton tower on multi-pile structure.	Higher intensity beam toward entrance to Annapolis Harbor and toward south approach to bay.
		*			*		6/03
19790	Naval Station Ramp Obstruction Daybeacon	38 58 52 N 76 27 55 W				NW on pile worded DANGER ROCK.	
		*					6/03
Severn River							
19935	Weems Creek Junction Daybeacon WC	39 00 04 N 76 29 56 W				JG on pile.	
		*					6/03
Mill Creek							
20030	- LIGHT 2M	38 59 34 N 76 26 49 W	FI R 2.5s	14	3	TR on pile.	
		*					6/03
23490	- Lighted Bell Buoy 12		FI R 4s		4	Red.	Replaced by lighted buoy of lower intensity from Dec. 1 to Mar. 15.
					*		6/03
23680	- Lighted Bell Buoy 1	38 12 21 N 75 55 55 W	FI G 4s		4	Green.	Replaced by lighted buoy of lower intensity from Dec. 1 to Mar. 15.
					*		6/03
27600	- Channel Lighted Buoy 3		FI G 4s		4	Green.	Replaced by unlighted ice buoy from Nov. 25 to Apr. 1.
					*		6/03
27645	- Channel Lighted Buoy 11		FI G 4s		4	Green.	Replaced by unlighted ice buoy from Nov. 25 to Apr. 1.
					*		6/03
Northeast River							
27835	- Lighted Buoy 2	39 29 12 N 75 59 56 W	FI R 4s		4	Red.	Replaced by unlighted ice buoy from Nov. 25 to Apr. 10.
					*		6/03
29235	- LIGHT 21		FI G 4s	15	4	SG on pile.	
				*			6/03

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2002

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
Beaufort Inlet							
29328 720	- Channel Lighted Whistle Buoy BM		Mo (A) W		6	Red and white with red sperical topmark.	RACON: M(– –). * 6/03

CORRECTIONS TO C. G. LIGHT LIST, VOLUME III ATLANTIC AND GULF COAST, 2002

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
4800	- UPPER RANGE FRONT LIGHT	32 04 23 N 80 57 28 W	Q R	30		KRW on skeleton tower on piles.	Visible 2° each side of rangeline. * 6/03
Naples Bay Channel							
17595	- Daybeacon 25	26 06 47 N 81 47 14 W				SG on pile.	* 6/03
22515	- Lighted Buoy 1	27 39 33 N 82 35 56 W	Q G		3	Green.	* 6/03
24715 60525	- LIGHT 4	27 41 41 N 82 36 32 W	Q R	16	3	TR-TY on pile.	* 6/03
60525 24715	- LIGHT 4	27 41 41 N 82 36 32 W	Q R	16	3	TR-TY on pile.	* 6/03

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2002

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
1568	- SUBMERGED JETTY LIGHT M	32 41 11 N 117 13 37 W	FI W 4s	15	4	NW on pile worded: DANGER SUBMERGED JETTY.	* 6/03
3640	- SOUTH JETTY LIGHT 2	34 09 22 N 119 16 10 W	FI R 2.5s	35		Rectangular concrete.	The fog signal can be activated upon request to the Coast Guard via VHF-FM Ch 16. HORN: 1 blast ev 15s (1s bl). * 6/03
3845	- Lighted Buoy 2		FI R 4s		3	Red.	Lighted from May 1 to Oct. 1. * 6/03
3930 250	- Gong Buoy 18EB	35 23 06 N 120 53 12 W				Red.	* 6/03

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI PACIFIC COAST AND PACIFIC ISLANDS, 2002

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
4683	- TURNING BASIN LIGHT A	37 47 42 N 122 17 22 W	Iso W 6s	18	4	NG on pile.	
		*					6/03
5770	- Lighted Buoy 1	37 55 46 N 122 25 42 W	FL G 4s				Green 6/03
SACRAMENTO AND SAN JOAQUIN RIVER (Chart 18661)							
Sacramento River							
7620	- LIGHT 2	38 10 38 N 121 39 53 W	Q R	15		TR on pile	6/03
8105	- DIRECTIONAL LIGHT	39 25 36 N 123 48 24 W	F W	15	1	On pile.	Visible white light in center of channel (103.5°T-106.5°T); red light when right of inbound channel (100°T-103.5°T); green light when left of inbound channel (106.5°T-110°T). 6/03
			*				6/03
8165	- ENTRANCE RANGE FRONT LIGHT	40 45 05 N 124 13 36 W	Q G	20		KRW on pile.	Visible 5° each side of rangeline. Operates continuously. * 6/03
8170	- ENTRANCE RANGE REAR LIGHT 268 yards, 141.5° from front light.		Oc G 4s	38		KRW on pile.	Operates continuously. * 6/03
8486	- Buoy Q					White can with orange bands.	* 6/03

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII LIGHT LIST, 2002

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
Constellation Nuclear Security Zone							
2060	-No Entry Bouy A	43 31 00 N 76 25 42 W				White can with orange exclusion symbol and worded NO ENTRY.	Replaced by spar from Nov. 1 to Apr. 15. Private aid. * 6/03
2271.3	- No Entry Buoy D	43 17 18 N 77 18 42 W				White can with orange bands and exclusion symbol worded NO ENTRY.	Private aid. 6/03
4345	- Lighted Buoy 5		FI G 4s		4	Green.	Maintained from Apr. 15 to Nov. 14. * 6/03

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII LIGHT LIST, 2002

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
4605	- Lighted Buoy 6		FI R 4s		4	Red.	Replaced by nun from Dec. 7 to Apr. 14. * 6/03
4725	- RANGE FRONT LIGHT	41 28 36 N 82 41 48 W	Q G	33 10	9	KRW on skeleton tower.	Visible on range line only. Higher intensity on rangeline only. * 6/03
5255	PLEASANT POINTE NORTH PIER LIGHT	41 32 24 N 82 42 54 W	FI W	16 5		On post.	Maintained from Apr. 15 to Nov. 30. Private aid. * 6/03
6050	- Entrance Light 2	41 49 30 N 83 11 36 W	FI R 2.5s	44 13	13	TR on tower with red band.	RACON: M (— —) BELL: 1 strike ev 30s. HORN: 1 blast ev 15s (1s bl). Standby Signal. Operates year round. * 6/03
6465	- RANGE REAR LIGHT 860 feet, 290° from front light.	41 49 47 N 83 24 57 W	FR	47 14		On pile.	Private aid. * 6/03
7195	Livingstone Channel Upper Entrance Light (C)	42 08 12 N 83 07 18 W	AI WR 10s	40 12	15	White circular tower mounted on white square crib. 20	Emergency light FI (2) W 15s. HORN: (two-tone) 1 blast ev 15s (4s bl). Operates year round * 6/03
8575	- Buoy 31					Green can.	* 6/03
11170	ALABASTER TRAMWAY RANGE REAR LIGHT 170 feet, 270° from front light.		FR	70 21		Gray box.	Private aid. * 6/03
<p>*Change Note to Read:</p> <p>Mackinaw Bridge</p> <p><i>*Buoys maintained from Apr. 28 to Dec. 7.</i></p>							
12625	- Lighted Bell Buoy 1	45 48 24 N 84 42 30 W	FI G 4s		4	Green.	6/03
14191	GEORGE KEMP MARINA EAST LIGHT	46 30 01 N 84 20 11 W	FI G 4s	12 4		Metal tower.	Maintained from May 1 to Oct. 31. Private aid. * 6/03

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII LIGHT LIST, 2002							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
14192	GEORGE KEMP MARINA WEST LIGHT	46 30 02 N 84 20 14 W	FI R 4s	12 4		Piling with metal tower.	Maintained from May 1 to Oct. 31. Private aid.
						*	6/03
15150	LAC LA BELLE NORTH PIERHEAD LIGHT		FI R 4s	25 8	4	2 TR on gray pole.	
						*	6/03
15155	<i>Keweenaw Point Lighted Buoy 1</i>		FI G 4s		4	Green.	Maintained from May 14 to Oct. 14.
							*
							6/03
16604	- HARBOR OF REFUGE SOUTH BREAKWATER LIGHT	47 31 14 N 90 55 28 W	Iso W 4s	22 7		NW on tower worded CAUTION.	Private aid. Ra ref.
							6/03
	*Delete Headings:						
	*BEAVER BAY TO PIGEON POINT (Chart 14967)						
	*Taconite Harbor						
16605	- HARBOR OF REFUGE BREAKWATER LIGHT 3	47 31 16 N 90 55 25 W	FI G 4s	22 7		SG on tower.	Private aid. Ra ref.
	*	*		*		*	*
							6/03
16606	- HARBOR OF REFUGE INNER LIGHT	47 31 17 N 90 55 25 W	Q R	17 5		TR on tower.	Visible from 284° to 336°. Private aid.
							6/03
16770	<i>Middle Island Passage Lighted Bell Buoy 2</i>	48 05 27 N 88 34 20 W	FI R 4s		4	Red.	Replaced by nun from Oct 14 to May 28.
							*
							6/03
	*Change Heading to Read:						
	*BIG TRAVERSE BAY (CHART 6211) (C)						
16925	PENASSE ISLAND LIGHT (C)	49 22 18 N 94 57 30 W	FI W 4s	37 11	6	Red and white rectangular daymark on circular mast. 20	Visible from 181° to 076°.
							6/03
	*Add Heading:						
	*LAKE OF THE WOODS (Chart 14999)						
16930	<i>Pine Creek Lighted Buoy 2</i>		FI R 4s		3	Red.	
							6/03
18395	- SOUTH PIERHEAD LIGHT		FI R 6s	30 9	6	TR on post.	
			*				6/03
	Suttons Bay						
18425	- INNER LIGHT		FI R 6s	27 8	4	TR on post.	
							6/03

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VII LIGHT LIST, 2002

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
18815	BANK POINT LIGHT Marks south side of shoal.		FI G 4s	24 7	5	SG on post on concrete pier.	* 6/03
19800	- Harbor Breakwater South End Light	41 43 34 N 87 29 36 W	AI WR 10s 0.2s W fl 4.8s ec. 0.2s R fl 4.8s ec.	50 15	W 15 R 12	White square skeleton tower with red band. Lower half open.	HORN: 1 blast ev 15s (2s bl). Operates continuously from Apr. to Dec. * 6/03
22010	Peshtigo River Entrance Lighted Bell Buoy 2						Remove from list. * 6/03
*22014	Oconto Harbor Lighted Bell Buoy	44 53 00 N 87 46 00 W	FI R 4s		4	Red.	Maintained from May 1 to Nov. 14. 6/03

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.