

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME I LIGHT LIST, 2003							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*8496	- CG Mooring Buoy					White and blue.	19/03
*13697	Cape Wind Meteorological Tower Lights MT (2)	41 28 19 N 70 18 53 W	Mo (U) Y	35	4	Monopole steel tower mounted on a pile supported platform marked "MT".	Private aid. HORN: Mo (U) (**-). 19/03
39380	- LIGHT	44 41 29 N 73 23 07 W	FI W 4s	75	7	On red skeleton tower.	Higher intensity beam southward. 19/03
		*					19/03
39810	SPLIT ROCK POINT LIGHT S	44 16 06 N 73 19 19 W	FI W 4s	93	7	NB on red skeleton tower.	19/03
		*					19/03

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2003							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*1074	- Buoy 35A						19/03
6996	LIGHT 10		FI R 4s	15	3	TR on pile.	19/03
						*	19/03
14980	- CHANNEL LIGHT 6						<i>Remove from list.</i> * 19/03
14981	- Lighted Buoy 6		FI R 2.5s		3	Red.	19/03
	*		*		*	*	19/03
24500	- Daybeacon 4	38 16 35 N 76 09 29 W				TR on pile.	Ra ref. 19/03
		*					19/03
24505	- LIGHT 5		FI G 4s	15	4	SG on pile structure with small black house.	19/03
				*			19/03
24510	- Daybeacon 6	38 18 37 N 76 09 46 W				TR on pile.	Ra ref. 19/03
		*					19/03
24525	- LIGHT 12		FI R 4s	15	3	TR on multi-pile structure.	19/03
				*		*	19/03
24530	HONGA RIVER - BACK CREEK ENTRANCE CHANNEL LIGHT 1 20 feet outside channel limit.	38 18 54 N 76 12 53 W	FI G 4s	15	4	SG on multi-pile structure.	19/03
		*					19/03

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2003

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
24545	- CHANNEL LIGHT 15		FI G 6s	15	3	SG on multi-pile structure.	19/03
						*	
24550	- CHANNEL LIGHT 17	38 21 04 N 76 13 05 W	FI G 4s	15	3	SG on pile.	19/03
		*				*	
Tar Bay							
24580	- CHANNEL LIGHT 1	38 21 07 N 76 16 20 W	FI G 4s	15	5	SG on multi-pile structure.	19/03
						*	
24585	- CHANNEL LIGHT 2	38 21 05 N 76 15 56 W	FI R 4s	15	3	TR on multi-pile structure.	19/03
						*	Light equipment removed from Dec. 1 to Mar. 15.
24590	- CHANNEL LIGHT 3	38 21 06 N 76 15 41 W	FI G 4s	15	3	SG on multi-pile structure.	19/03
						*	Light equipment removed from Dec. 1 to Mar. 15.
24595	- CHANNEL LIGHT 4	38 20 53 N 76 15 26 W	FI R 4s	15	3	TR on multi-pile structure.	19/03
						*	Light equipment removed from Dec. 1 to Mar. 15.
24600	- CHANNEL LIGHT 5	38 20 49 N 76 14 51 W	FI G 6s	15	3	SG on multi-pile structure.	19/03
						*	Light equipment removed from Dec. 1 to Mar. 15.
24605	- CHANNEL LIGHT 6	38 20 36 N 76 14 23 W	FI R 4s	15	3	TR on multi-pile structure.	19/03
						*	Light equipment removed from Dec. 1 to Mar. 15.
24610	- CHANNEL LIGHT 7	38 20 39 N 76 14 09 W	FI G 4s	15	3	SG on multi-pile structure.	19/03
						*	Light equipment removed from Dec. 1 to Mar. 15.
24615	- CHANNEL LIGHT 8		FI R 4s	15	3	TR on multi-pile structure.	19/03
						*	
24620	Tyler Cove Channel Daybeacon 1					SG on multi-pile structure.	19/03
						*	
24625	Tyler Cove Channel Daybeacon 2					TR on multi-pile structure.	19/03
						*	
24655	- Daybeacon 3	38 30 14 N 76 16 15 W				SG on multi-pile structure.	19/03
		*				*	

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2003							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
24660	- LIGHT 4	38 30 08 N 76 16 15 W	FI R 4s	15	3	TR on multi-pile structure.	Light equipment removed from Dec. 1 to Mar. 15.
						*	19/03
24685	- LIGHT 9	38 29 41 N 76 16 42 W	FI G 2.5s	15	3	SG on multi-pile structure.	
						*	19/03
24690	- LIGHT 10	38 29 07 N 76 17 08 W	FI R 4s	15	3	TR on multi-pile structure.	
						*	19/03
24730	- LIGHT 9		FI G 4s	15	3	SG on multi-pile structure.	
						*	19/03
Madison Bay							
24735	- LIGHT 2	38 31 51 N 76 13 32 W	FI R 4s	15	3	TR on multi-pile structure.	
						*	19/03
24920	ISLAND CREEK LIGHT 1	38 39 19 N 76 09 33 W	FI G 4s	15	4	SG on multi-pile structure.	
						*	19/03
24975	- CHANNEL LIGHT 20	38 36 01 N 76 06 52 W	FI R 4s	15	4	TR on multi-pile structure.	Light equipment removed from Dec. 1 to Mar. 15.
						*	* 19/03
25055	CAMBRIDGE SEWER OUTFALL WARNING LIGHT	38 34 22 N 76 03 10 W	Q W	15	4	NW on pile worded DANGER SUBMERGED PIPE.	
						*	19/03
Broad Creek							
25530	- LIGHT 1	38 41 39 N 76 14 58 W	FI G 4s	15	4	SG on pile.	Light equipment removed from Dec. 1 to Mar. 15.
						*	19/03
Balls Creek							
25540	- LIGHT 1	38 43 12 N 76 16 11 W	FI G 4s	15	4	SG on multi-pile structure.	Light equipment removed from Dec. 1 to Mar. 15.
						*	19/03

CORRECTIONS TO C. G. LIGHT LIST, VOLUME III LIGHT LIST, 2003							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
590	St. Augustine Light	29 53 08 N 81 17 19 W	FFI W 30s	161	F 19 FI 24	Conical tower, white base with black cornice; black and white spirally-banded shaft; black below lantern gallery deck; red above.	Private aid.
						*	19/03

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME III LIGHT LIST, 2003

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
965	Conch Reef Buoy 12 Near seaward edge of reef.	24 56 48 N 80 27 26 W				Red nun.	
		*					19/03
ALLIGATOR REEF TO SOMBRERO KEY (Chart 11452)							
985	Tennessee Reef East Lighted Buoy 18	24 47 32 N 80 41 36 W	FI R 2.5s		5	Red.	
		*					19/03
1040 14800	Key West Entrance Lighted Whistle Buoy KW	24 27 41 N 81 48 02 W	Mo (A) W		6	Red and white stripes with red spherical topmark.	
		*					19/03
KEY WEST HARBOR AND APPROACHES (Chart 11441)							
Key West Harbor Main Channel							
14800 1040	- Entrance Lighted Whistle Buoy KW	24 27 41 N 81 48 02 W	Mo (A) W		6	Red and white stripes with red spherical topmark.	
		*					19/03
*Add Heading: *Essex River							
*48905.1	- Daybeacon 7					SG on pile.	Private aid.
							19/03
*48905.2	- Daybeacon 8					TR on pile.	Private aid.
							19/03
*48905.3	- Daybeacon 9					SG on pile.	Private aid.
							19/03
*Add Headings: *Biscayne Bay *Dinner Key Seaplane Channel							
48910	BISCAYNE BAY DANGER SHOAL LIGHT	25 42 35 N 80 11 59 W	FI W 4s	16	4	NW on pile worded DANGER SHOAL.	
							19/03

CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV LIGHT LIST, 2003

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
North Shore Channel							
9605	- CUT A RANGE FRONT LIGHT	30 11 50 N 89 46 33 W	Q W	20		KRW on skeleton tower on piles.	Visible on range line only.
		*					19/03
9650	- CUT B RANGE FRONT LIGHT	30 11 47 N 89 46 27 W	Q W	20		KRW on skeleton tower on dolphin.	Visible on range line only.
		*					19/03

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV LIGHT LIST, 2003							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
17365	- Daybeacon 4						<i>Remove from list.</i>
							* 19/03
17375	- LIGHT 6						<i>Remove from list.</i>
							* 19/03
TIMBALIER AND TERREBONNE BAYS (Chart 11357)							
17385	CAILLOU BOCA ENTRANCE LIGHT 2	29 04 04 N 90 47 40 W	F I R 2.5s	17	4	TR on piles.	
	*	*	*	*	*	*	19/03
22950	LOWER GALVESTON BAY INNER RANGE FRONT LIGHT	29 30 30 N 94 52 22 W	F I W 2.5s (Day) F I G 2.5s (Night) F I G 2.5s	42 39 55	4	On piles.	DAY: Visible 2° each side of range line. NIGHT: Visible all around, higher intensity on range line.
			*	*	*		19/03
23217	MORGANS POINT APPROACH OUTER RANGE FRONT PASSING LIGHT		Q G	32	5	On same structure as Morgans Point Approach Outer Range Front Light.	
			*				19/03
25655	FREEPORT JETTY INBOUND RANGE REAR LIGHT 2,317 yards, 317.5° from front light.		Oc W 4s (Day) Oc G 4s (Night)	143 146		KRW on skeleton tower on block.	Visible 2° each side of rangeline. Lighted throughout 24 hours.
				*		*	19/03
26010	- RANGE B FRONT LIGHT	28 25 41 N 96 19 37 W	Q W	20		KRW on skeleton tower on block.	Visible 2° each side of rangeline.
		*				*	19/03
26045	- LIGHT 17	28 26 29 N 96 20 50 W	F I G 2.5s	17	4	SG on pile.	Ra ref.
		*					19/03
Viola Channel							
27705	- RANGE G FRONT LIGHT	27 50 36 N 97 30 54 W	Q G	20		KRW on skeleton tower on sills.	Visible all around; higher intensity on rangeline.
				*		*	19/03
27770	- INNER RANGE FRONT LIGHT	27 52 30 N 97 15 00 W	Q G	17		KRW on skeleton tower on piles.	Visible 2° each side of rangeline. Ra ref.
				*			19/03
27835	- LIGHT 14 170 feet outside channel limit.		F I R 4s	17	3	TR on skeleton tower.	
				*			19/03
27850	- LIGHT 17		F I G 2.5s	17	3	SG on dolphin.	Ra ref.
					*		19/03

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV LIGHT LIST, 2003

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
28105	- RANGE REAR LIGHT 800 yards, 267.5° from front light.		Oc R 4s	62		KRW on skeleton tower on block.	Visible 2° each side of rangeline. F R aircraft warning light on tower.
				*		*	19/03
28150	- ENTRANCE RANGE FRONT LIGHT	26 03 57 N 97 10 16 W	Q G	37		KRW on skeleton tower on piles.	Visible 2° each side of rangeline.
		*					19/03
28260	- LIGHT 16	26 03 33 N 97 10 49 W	FI R 2.5s	17	3	TR on dolphin.	Ra ref.
		*			*		19/03
28280	- LIGHT 27		FI G 2.5s	17	4	SG on pile.	Ra ref.
					*		19/03
28300 40725	- LEADING LIGHT	26 02 51 N 97 12 26 W	Iso W 6s	17	6	NB on pile.	
		*					19/03
28350 40740	- RANGE C FRONT LIGHT	26 02 17 N 97 12 43 W	Q G Q G	25 27	3	KRW-I on skeleton tower on piles.	Visible all around; higher intensity on range line.
		*	*	*	*		19/03
28375 40765	- LIGHT 33		FI G 4s	17	4	SG-SY on pile.	Ra ref.
				*	*		19/03
28380 40770	- RANGE E FRONT LIGHT	26 01 27 N 97 14 37 W	Q W Q W	33 35	5	KRW-I on skeleton tower on piles.	For downbound traffic. Visible all around; higher intensity 2° each side of rangeline.
			*	*	*		19/03
28395 40785	- RANGE B FRONT LIGHT	26 00 52 N 97 15 46 W	Q R Q R	25 27	3	KRW-I on skeleton tower on piles.	Visible all around; higher intensity on rangeline.
		*	*	*	*		19/03
28420 40825	- RANGE D FRONT LIGHT	25 58 58 N 97 19 57 W	Q W Q W	25 27	5	KRW-I on skeleton tower.	Visible all around; higher intensity on rangeline.
		*	*	*	*		19/03
28430 40810	- LIGHT 40		FI R 4s	17	4	TR-TY on skeleton tower on piles.	
				*	*		19/03
28435 40815	- RANGE G FRONT LIGHT	25 58 44 N 97 19 22 W	Q G Q G	25 27	3	KRW-I on skeleton tower on piles.	Visible all around; higher intensity on rangeline.
		*	*	*	*		19/03
28460 40845	- RANGE F FRONT LIGHT	25 57 02 N 97 24 11 W	FI W 2.5s (Day) FI G 2.5s (Night)	47 45		KRW-I on skeleton tower.	Visible 2° each side of rangeline.
			*	*			19/03

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV LIGHT LIST, 2003							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
28465 40855	- RANGE F REAR LIGHT 3,870 yards, 249° from front light.		Oc W 4s (Day) Oc G 4s (Night)	95 98		KRW on skeleton tower.	Visible 2° each side of rangeline. Lighted throughout 24 hours.
			*	*			19/03
28805	- LIGHT 28		Q R	17	3	TR-TY on dolphin.	
				*			19/03
28920	- LIGHT 58		FI R 6s	17	4	TR-TY on dolphin.	
				*			19/03
28940	- LIGHT 64		FI R 4s	17	3	TR-TY on dolphin.	Ra ref.
				*			19/03
29095	- RANGE FRONT LIGHT	29 43 21 N 84 58 48 W	Q G Q G	15 17	3	KRW-I on dolphin.	Visible all around; higher intensity on rangeline.
			*	*	*		19/03
32515	- LIGHT 9		FI G 4s	17	4	SG on pile.	Ra ref.
					*		19/03
40725 28300	PORT ISABEL CHANNEL LEADING LIGHT	26 02 51 N 97 12 26 W	Iso W 6s	17	6	NB on pile.	
		*					19/03
40740 28350	- RANGE C FRONT LIGHT	26 02 12 N 97 12 42 W	Q G Q G	25 27	3	KRW-I on skeleton tower on piles.	Visible all around; higher intensity on range line.
			*	*	*		19/03
40765 28375	- LIGHT 33		FI G 4s	17	4	SG-SY on pile.	Ra ref.
				*	*		19/03
40770 28380	- RANGE E FRONT LIGHT	26 01 27 N 97 14 37 W	Q W Q W	33 35	5	KRW-I on skeleton tower on piles.	For downbound traffic. Visible all around; higher intensity 2° each side of rangeline.
			*	*	*		* 19/03
40785 28395	- RANGE B FRONT LIGHT	26 00 54 N 97 15 42 W	Q R Q R	25 27	3	KRW-I on skeleton tower on piles.	Visible all around; higher intensity on rangeline.
			*	*	*		* 19/03
40810 28430	- LIGHT 40		FI R 4s	17	4	TR-TY on skeleton tower on piles.	
				*	*		19/03
40815 28435	- RANGE G FRONT LIGHT	25 58 48 N 97 19 00 W	Q G Q G	25 27	3	KRW-I on skeleton tower on piles.	Visible all around; higher intensity on rangeline.
			*	*	*		* 19/03

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV LIGHT LIST, 2003

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
40825 28420	- RANGE D FRONT LIGHT	25 58 30 N 97 19 54 W	Q W Q W	25 27	5	KRW-I on skeleton tower.	Visible all around; higher intensity on rangeline. * 19/03
40845 28460	- RANGE F FRONT LIGHT	25 57 02 N 97 24 11 W	FI W 2.5s (Day) FI G 2.5s (Night)	47 45		KRW-I on skeleton tower.	Visible 2° each side of rangeline. * 19/03
40855 28465	- RANGE F REAR LIGHT 3,870 yards, 249° from front light.		Oc W 4s (Day) Oc G 4s (Night)	95 98		KRW on skeleton tower.	Visible 2° each side of rangeline. Lighted throughout 24 hours. * 19/03

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI LIGHT LIST, 2003

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
4820	<i>San Francisco Bay Preferred Channel Lighted Buoy SC</i>	37 46 32 N 122 21 57 W	FI G (2+1)			Green and red.	* 19/03
*17136	PORT OF TACOMA TERMINAL NO. 8 LIGHT A	47 16 14 N 122 25 14 W	Q Y	16		On dolphin.	Private aid. 19/03
*17137	PORT OF TACOMA TERMINAL NO. 8 LIGHT B	47 16 13 N 122 25 13 W	Q Y	16		On corner of pier.	Private aid. 19/03
*17815	BANGOR SECURITY BARRIER FLOAT LIGHTS (103)	47 45 03 N 122 44 03 W	Q Y			Gray floating barrier.	Navy maintained. Floating steel barrier system marked by lights. 103 Q Y 19/03
*18089	BREMERTON SECURITY BARRIER FLOAT LIGHTS (152)	47 33 12 N 122 38 19 W	Q Y			Gray floating barrier.	Navy maintained. Floating steel barrier system marked by lights. 152 Q Y 19/03
<p>*Delete Headings: *HECATE STRAIT TO ETOLIN ISLAND (Chart 17420) *Dixon Entrance</p>							
21834	Island Point Coast Guard Mooring Buoy						<i>Remove from list.</i> * 19/03
<p>*Add Headings: *HECATE STRAIT TO ETOLIN ISLAND (Chart 17420) *Dixon Entrance</p>							
21835	LORD ROCK LIGHT	54 43 33 N 130 49 13 W	FI W 4s	38	7	NR on skeleton tower.	19/03

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added. Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI LIGHT LIST, 2003							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
27305	- Buoy 11	55 02 10 N 163 25 04 W				Green can.	
		*					19/03
	Garapan Channel						
30917	- LIGHT 1	15 11 49 N 145 42 31 E	FI G 2.5s	20		On concrete lighthouse.	Private aid.
		*					19/03

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.